

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P277898

Luminaire Tested: **LDA2B059024D010 EU2B05SP159024 2LBAD1H**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P277898
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-1811-033-1)
Test Lab: INNOVATION CENTER(G2)
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LDA2B059024D010 EU2B05SP159024 2LBAD1H
Description: PORTFOLIO 2IN ADJ 500 LUMEN LED LUMINAIRE WITH SPOT OPTIC AND 2in
ADJ spun Refl, Self-Flanged, H
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 571.5 lumens
Efficiency: N/A
Efficacy: 81.6 lumens/watt
Spacing Criteria (0/90/45): 0.28 / 0.28 / 0.28
Luminous Opening: Circular (Dia: 0.17' x H: 0')
CIE Type: Direct


Input Watts (W): 7
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P277898

CATALOG NUMBER: LDA2B059024D010 EU2B05SP159024 2LBAD1H

Luminous Intensity Polar Plot





TEST NUMBER: P277898

CATALOG NUMBER: LDA2B059024D010 EU2B05SP159024 2LBAD1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

| | | | | | | | | | | | | | | | | | | | | | |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|---|
| RF | 20 | | | | 20 | | | | 20 | | | | 20 | | | | 20 | | | | |
| RC | 80 | | | | 70 | | | | 50 | | | | 30 | | | | 10 | | | 0 | |
| RW | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 0 |
| RCR | | | | | | | | | | | | | | | | | | | | | |
| 0 | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 | 106 | 106 | 106 | 102 | 102 | 102 | 100 | | | |
| 1 | 116 | 114 | 112 | 110 | 113 | 112 | 110 | 109 | 108 | 106 | 105 | 104 | 103 | 102 | 101 | 100 | 99 | 98 | | | |
| 2 | 112 | 109 | 107 | 104 | 110 | 108 | 105 | 103 | 105 | 103 | 101 | 102 | 100 | 99 | 99 | 98 | 97 | 96 | | | |
| 3 | 109 | 105 | 102 | 100 | 108 | 104 | 101 | 99 | 102 | 99 | 98 | 100 | 98 | 96 | 97 | 96 | 95 | 93 | | | |
| 4 | 107 | 102 | 99 | 96 | 105 | 101 | 98 | 96 | 99 | 97 | 95 | 98 | 95 | 94 | 96 | 94 | 93 | 92 | | | |
| 5 | 104 | 99 | 96 | 93 | 103 | 99 | 95 | 93 | 97 | 94 | 92 | 96 | 93 | 91 | 94 | 92 | 91 | 90 | | | |
| 6 | 102 | 97 | 93 | 91 | 101 | 96 | 93 | 91 | 95 | 92 | 90 | 94 | 91 | 89 | 93 | 91 | 89 | 88 | | | |
| 7 | 100 | 95 | 91 | 89 | 99 | 94 | 91 | 88 | 93 | 90 | 88 | 92 | 90 | 88 | 91 | 89 | 87 | 86 | | | |
| 8 | 98 | 93 | 89 | 87 | 97 | 92 | 89 | 87 | 91 | 88 | 86 | 90 | 88 | 86 | 90 | 87 | 86 | 85 | | | |
| 9 | 96 | 91 | 87 | 85 | 95 | 90 | 87 | 85 | 90 | 87 | 85 | 89 | 86 | 84 | 88 | 86 | 84 | 83 | | | |
| 10 | 94 | 89 | 86 | 83 | 94 | 89 | 85 | 83 | 88 | 85 | 83 | 87 | 85 | 83 | 87 | 85 | 83 | 82 | | | |

AVERAGE LUMINANCE (cd/sqm):

| | |
|-----|---------|
| | 0° |
| 0° | 2581466 |
| 5° | 2058095 |
| 10° | 893485 |
| 15° | 308707 |
| 20° | 126583 |
| 25° | 57158 |
| 30° | 23015 |
| 35° | 10721 |
| 40° | 5796 |
| 45° | 2163 |
| 50° | 1305 |
| 55° | 946 |
| 60° | 592 |
| 65° | 350 |
| 70° | 433 |
| 75° | 0 |
| 80° | 0 |
| 85° | 0 |



TEST NUMBER: P277898

CATALOG NUMBER: LDA2B059024D010 EU2B05SP159024 2LBAD1H

ZONAL LUMENS:

| Zone | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10° | 314.1 | 55.0 |
| 10°-20° | 188.6 | 33.0 |
| 20°-30° | 51.9 | 9.1 |
| 30°-40° | 12.4 | 2.2 |
| 40°-50° | 3.1 | 0.5 |
| 50°-60° | 1.0 | 0.2 |
| 60°-70° | 0.4 | 0.1 |
| 70°-80° | 0.0 | 0.0 |
| 80°-90° | 0.0 | 0.0 |
| 90°-100° | 0.0 | 0.0 |
| 100°-110° | 0.0 | 0.0 |
| 110°-120° | 0.0 | 0.0 |
| 120°-130° | 0.0 | 0.0 |
| 130°-140° | 0.0 | 0.0 |
| 140°-150° | 0.0 | 0.0 |
| 150°-160° | 0.0 | 0.0 |
| 160°-170° | 0.0 | 0.0 |
| 170°-180° | 0.0 | 0.0 |
| 0°-30° | 554.6 | 97.1 |
| 0°-40° | 567.0 | 99.2 |
| 0°-60° | 571.0 | 99.9 |
| 0°-90° | 571.5 | 100.0 |
| 90°-120° | 0.0 | 0.0 |
| 90°-150° | 0.0 | 0.0 |
| 90°-180° | 0.0 | 0.0 |
| 0°-180° | 571.5 | 100.0 |

CANDELA DISTRIBUTION:

| | 0° | Flux |
|-----|------|------|
| 0° | 5232 | |
| 5° | 4156 | 314 |
| 15° | 604 | 189 |
| 25° | 105 | 52 |
| 35° | 18 | 12 |
| 45° | 3 | 3 |
| 55° | 1 | 1 |
| 65° | 0 | 0 |
| 75° | 0 | 0 |
| 85° | 0 | 0 |
| 90° | 0 | |



TEST NUMBER: P277898

CATALOG NUMBER: LDA2B059024D010 EU2B05SP159024 2LBAD1H

CANDELA DISTRIBUTION (FULL):

| | 0° |
|-------|--------|
| 0° | 5232.4 |
| 1° | 5174.5 |
| 2° | 5035.9 |
| 3° | 4824.4 |
| 4° | 4526.1 |
| 5° | 4155.7 |
| 6° | 3703.4 |
| 7° | 3208.0 |
| 8° | 2687.5 |
| 9° | 2208.7 |
| 10° | 1783.5 |
| 11° | 1423.6 |
| 12° | 1133.1 |
| 13° | 913.8 |
| 14° | 739.3 |
| 15° | 604.4 |
| 17.5° | 375.2 |
| 20° | 241.1 |
| 22.5° | 158.1 |
| 25° | 105.0 |
| 27.5° | 67.5 |
| 30° | 40.4 |
| 32.5° | 25.4 |
| 35° | 17.8 |
| 37.5° | 13.0 |
| 40° | 9.0 |
| 42.5° | 5.4 |
| 45° | 3.1 |
| 47.5° | 2.3 |
| 50° | 1.7 |
| 52.5° | 1.4 |
| 55° | 1.1 |
| 57.5° | 0.8 |
| 60° | 0.6 |
| 62.5° | 0.6 |
| 65° | 0.3 |
| 67.5° | 0.3 |
| 70° | 0.3 |
| 72.5° | 0.0 |
| 75° | 0.0 |
| 77.5° | 0.0 |
| 80° | 0.0 |
| 82.5° | 0.0 |



TEST NUMBER: P277898

CATALOG NUMBER: LDA2B059024D010 EU2B05SP159024 2LBAD1H

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







| | | |
|-------|--|-----|
| 85° | | 0.0 |
| 87.5° | | 0.0 |



(END OF REPORT)