

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P492722

Luminaire Tested: **LDA2B059024R30D010 2LBPIN1H**

Issue Date: 3/12/2021

This test was performed under the Supervised Manufacturer's Testing Program. The results of this test have not been influenced by sources from within Cooper Lighting Solutions or from external interests.



**Test Information**

Test Method: LM-79-08  
Report Number: P492722  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2011-037-14)  
Test Lab: INNOVATION CENTER  
Issue Date: 3/12/2021  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LDA2B059024R30D010 2LBPIN1H  
Description: 500 LUMEN 2IN ADJUSTABLE LED LUMINAIRE WITH 90 CRI LEDS AND 2400K CCT LEDS  
Light Source: -  
Ballast/Driver: -

Luminaire Equipment: Sample No.    Condition    Description

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 453.2 lumens  
Efficiency: N/A  
Efficacy: 64.7 lumens/watt  
Spacing Criteria (0/90/45): 0.48 / 0.48 / 0.46  
Luminous Opening: Circular (Dia: 0.17' x H: 0')  
CIE Type: Direct

Input Watts (W): 7  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT

TEST NUMBER: P492722

CATALOG NUMBER: LDA2B059024R30D010 2LBPIN1H

### Luminous Intensity Polar Plot





TEST NUMBER: P492722

CATALOG NUMBER: LDA2B059024R30D010 2LBPIN1H

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	115	113	111	109	113	111	109	108	107	106	104	103	102	101	100	99	98	97
2	111	108	105	102	109	106	103	101	103	101	99	100	98	97	97	96	95	93
3	108	103	100	97	106	102	99	96	99	97	94	97	95	93	95	93	92	90
4	104	99	95	92	103	98	94	92	96	93	91	94	92	90	93	90	89	87
5	101	95	91	88	100	95	91	88	93	90	87	91	89	86	90	88	86	85
6	98	92	88	85	97	91	88	85	90	87	84	89	86	84	88	85	83	82
7	96	89	85	82	95	89	85	82	87	84	81	86	83	81	85	83	81	80
8	93	86	82	79	92	86	82	79	85	81	79	84	81	79	83	81	78	77
9	90	84	80	77	90	83	80	77	83	79	77	82	79	76	81	78	76	75
10	88	81	77	75	87	81	77	75	80	77	75	80	77	74	79	76	74	73

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	878431
5°	837561
10°	679219
15°	415201
20°	181396
25°	67882
30°	28142
35°	13130
40°	6118
45°	3000
50°	1612
55°	602
60°	197
65°	233
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P492722

CATALOG NUMBER: LDA2B059024R30D010 2LBPIN1H

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	150.9	33.3
10°-20°	217.8	48.1
20°-30°	65.0	14.3
30°-40°	14.9	3.3
40°-50°	3.7	0.8
50°-60°	0.8	0.2
60°-70°	0.1	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	433.7	95.7
0°-40°	448.6	99.0
0°-60°	453.1	100.0
0°-90°	453.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	453.2	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	1780	
5°	1691	151
15°	813	218
25°	125	65
35°	22	15
45°	4	4
55°	1	1
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P492722

CATALOG NUMBER: LDA2B059024R30D010 2LBPIN1H

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	1780.5
1°	1776.4
2°	1758.4
3°	1746.3
4°	1723.7
5°	1691.2
6°	1646.8
7°	1593.8
8°	1526.3
9°	1444.2
10°	1355.8
11°	1261.3
12°	1154.0
13°	1038.5
14°	928.8
15°	812.9
16°	700.8
17°	590.4
18°	501.3
19°	414.9
20°	345.5
21°	280.0
22.5°	207.6
23°	187.1
24°	153.2
25°	124.7
26°	102.4
27°	85.3
28°	70.3
29°	58.9
30°	49.4
32.5°	32.3
35°	21.8
37.5°	14.5
40°	9.5
42.5°	6.2
45°	4.3
47.5°	3.1
50°	2.1
52.5°	1.4
55°	0.7
57.5°	0.5
60°	0.2
62.5°	0.2
65°	0.2



TEST NUMBER: P492722

CATALOG NUMBER: LDA2B059024R30D010 2LBPIN1H

**CANDELA DISTRIBUTION (continued):**

	0°
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)