

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P492888

Luminaire Tested: **LDA2B059027R20D010 2LBDL1MMS-30DEG TILT**

Issue Date: 3/8/2021

This test was performed under the Supervised Manufacturer's Testing Program. The results of this test have not been influenced by sources from within Cooper Lighting Solutions or from external interests.



Test Information

Test Method: LM-79-08
Report Number: P492888
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2011-037-2)
Test Lab: INNOVATION CENTER
Issue Date: 3/8/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LDA2B059027R20D010 2LBDL1MMS-30DEG TILT
Description: 500 LUMEN 2IN ADJUSTABLE LED LUMINAIRE WITH 90 CRI LEDS AND 2700K CCT LEDS
Light Source: -
Ballast/Driver: -

Luminaire Equipment: Sample No. Condition Description

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 335.8 lumens
Efficiency: N/A
Efficacy: 48.0 lumens/watt
Spacing Criteria (0/90/45): 2.56 / 0.56 / 1.2
Luminous Opening: Circular (Dia: 0.17' x H: 0')
CIE Type: Direct

Input Watts (W): 7
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P492888

CATALOG NUMBER: LDA2B059027R20D010 2LBDL1MMS-30DEG TILT

Luminous Intensity Polar Plot



— 0°-180° - - 45°-225° - - - 90°-270°



TEST NUMBER: P492888

CATALOG NUMBER: LDA2B059027R20D010 2LBDL1MMS-30DEG TILT

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20					
RC	80					70					50					30					10					0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																										
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100					100			
1	112	109	106	104	110	107	104	102	103	101	99	99	97	96	96	94	93	91					91			
2	105	100	95	91	103	98	93	90	95	91	88	91	88	86	89	86	84	82					82			
3	99	91	85	80	96	89	84	79	87	82	78	84	80	77	82	78	76	74					74			
4	92	83	76	71	90	82	75	70	79	74	70	77	73	69	75	71	68	66					66			
5	86	75	68	63	84	74	68	63	73	67	62	71	66	62	69	65	61	59					59			
6	80	69	62	56	78	68	61	56	66	60	56	65	59	55	63	59	55	53					53			
7	74	63	55	50	73	62	55	50	61	54	50	59	54	50	58	53	49	48					48			
8	69	57	50	45	68	57	50	45	56	49	45	54	49	44	53	48	44	43					43			
9	64	53	45	40	63	52	45	40	51	45	40	50	44	40	49	44	40	38					38			
10	60	48	41	36	59	48	41	36	47	41	36	46	40	36	45	40	36	34					34			

AVERAGE LUMINANCE (cd/sqm):

	0°	90°	180°
0°	5328	5328	5328
5°	10202	4705	3417
10°	24347	4108	2304
15°	141993	3269	919
20°	708258	2048	263
25°	1291396	708	0
30°	1514679	0	0
35°	1325747	0	0
40°	979002	0	0
45°	352906	0	0
50°	73453	0	0
55°	16859	258	0
60°	5328	296	0
65°	1167	584	0
70°	0	721	433
75°	0	953	0
80°	0	1421	0
85°	0	2830	0



TEST NUMBER: P492888

CATALOG NUMBER: LDA2B059027R20D010 2LBDL1MMS-30DEG TILT

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1.2	0.4
10°-20°	18.4	5.5
20°-30°	124.3	37.0
30°-40°	145.2	43.3
40°-50°	42.4	12.6
50°-60°	2.8	0.8
60°-70°	0.5	0.2
70°-80°	0.4	0.1
80°-90°	0.4	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	144.0	42.9
0°-40°	289.2	86.1
0°-60°	334.4	99.6
0°-90°	335.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	335.8	100.0

CANDELA DISTRIBUTION:

	0°	45°	90°	135°	180°	Flux
0°	11	11	11	11	11	
5°	21	15	10	8	7	3
15°	278	31	6	3	2	145
25°	2372	49	1	0	0	1050
35°	2201	26	0	0	0	1352
45°	506	5	0	0	0	466
55°	20	1	0	0	0	25
65°	1	0	0	0	0	2
75°	0	0	0	0	0	0
85°	0	0	0	0	0	0
90°	0	0	0	0	0	



TEST NUMBER: P492888

CATALOG NUMBER: LDA2B059027R20D010 2LBDL1MMS-30DEG TILT

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°	112.5°	135°	157.5°	180°
0°	10.8	10.8	10.8	10.8	10.8	10.8	10.8	10.8	10.8
2.5°	13.9	13.9	12.4	11.1	10.0	9.5	9.3	8.8	8.5
5°	20.6	18.0	14.9	11.6	9.5	8.8	8.0	7.2	6.9
7.5°	30.1	26.3	18.0	11.8	9.0	7.7	6.9	6.2	5.7
10°	48.6	37.8	22.1	11.8	8.2	6.7	5.7	4.9	4.6
12.5°	89.8	57.9	26.5	11.6	7.5	5.7	4.4	3.9	3.1
15°	278.0	119.9	31.4	11.1	6.4	4.4	3.3	2.1	1.8
17.5°	718.9	280.0	35.0	9.8	5.1	3.1	1.5	1.3	1.3
20°	1349.0	507.8	40.2	8.5	3.9	2.1	1.0	0.8	0.5
21°	1538.9	621.3	42.7	8.0	3.3	1.3	0.8	0.3	0.3
22°	1834.2	745.1	44.8	7.5	2.8	0.8	0.5	0.3	0.0
23°	2044.4	824.2	46.8	6.7	2.1	0.8	0.3	0.0	0.0
24°	2254.7	924.8	48.1	6.2	1.8	0.5	0.3	0.0	0.0
25°	2372.3	1008.7	48.6	5.7	1.3	0.3	0.0	0.0	0.0
26°	2469.1	1064.8	48.9	5.1	0.8	0.0	0.0	0.0	0.0
27°	2552.0	1129.9	48.4	4.6	0.8	0.0	0.0	0.0	0.0
28°	2599.1	1140.7	47.6	4.1	0.3	0.0	0.0	0.0	0.0
29°	2619.4	1127.6	45.3	3.6	0.3	0.0	0.0	0.0	0.0
30°	2658.8	1115.3	43.0	3.3	0.0	0.0	0.0	0.0	0.0
31°	2622.5	1074.3	40.2	2.8	0.0	0.0	0.0	0.0	0.0
32°	2480.5	1039.8	36.8	2.3	0.0	0.0	0.0	0.0	0.0
33°	2438.0	969.1	33.2	2.1	0.0	0.0	0.0	0.0	0.0
34°	2357.9	863.8	30.1	1.8	0.0	0.0	0.0	0.0	0.0
35°	2201.2	776.8	26.3	1.5	0.0	0.0	0.0	0.0	0.0
36°	2091.8	677.4	22.9	1.3	0.0	0.0	0.0	0.0	0.0
37°	1977.3	590.7	20.3	1.0	0.0	0.0	0.0	0.0	0.0
38°	1834.9	499.6	17.2	0.8	0.0	0.0	0.0	0.0	0.0
39°	1669.2	412.9	14.7	0.8	0.0	0.0	0.0	0.0	0.0
40°	1520.1	332.8	12.6	0.5	0.0	0.0	0.0	0.0	0.0
42.5°	938.2	190.0	7.5	0.5	0.0	0.0	0.0	0.0	0.0
45°	505.8	115.3	5.4	0.3	0.0	0.0	0.0	0.0	0.0
47.5°	232.9	53.8	3.9	0.3	0.0	0.0	0.0	0.0	0.0
50°	95.7	23.9	2.8	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	34.5	13.4	1.8	0.0	0.0	0.3	0.0	0.0	0.0
55°	19.6	7.7	1.0	0.3	0.3	0.3	0.3	0.0	0.0
57.5°	9.3	4.4	0.3	0.3	0.3	0.3	0.3	0.0	0.0
60°	5.4	2.3	0.3	0.3	0.3	0.5	0.3	0.0	0.0
62.5°	2.6	0.8	0.3	0.5	0.5	0.5	0.5	0.3	0.0
65°	1.0	0.3	0.5	0.5	0.5	0.8	0.5	0.3	0.0
67.5°	0.3	0.3	0.5	0.5	0.5	0.8	0.5	0.3	0.3
70°	0.0	0.3	0.5	0.5	0.5	0.8	0.5	0.3	0.3
72.5°	0.0	0.3	0.5	0.5	0.5	0.8	0.5	0.3	0.3
75°	0.0	0.3	0.5	0.5	0.5	0.5	0.5	0.3	0.0
77.5°	0.0	0.3	0.5	0.5	0.5	0.5	0.5	0.3	0.0
80°	0.0	0.3	0.5	0.5	0.5	0.5	0.5	0.3	0.0



TEST NUMBER: P492888

CATALOG NUMBER: LDA2B059027R20D010 2LBDL1MMS-30DEG TILT

CANDELA DISTRIBUTION (continued):

	0°	22.5°	45°	67.5°	90°	112.5°	135°	157.5°	180°
82.5°	0.0	0.3	0.5	0.5	0.5	0.5	0.5	0.3	0.0
85°	0.0	0.3	0.5	0.5	0.5	0.5	0.5	0.3	0.0
87.5°	0.0	0.3	0.5	0.5	0.5	0.5	0.3	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

(END OF REPORT)