

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P493204

Luminaire Tested: **LDA2B059030R45D010 2LBD1WH**

Issue Date: 3/8/2021

This test was performed under the Supervised Manufacturer's Testing Program. The results of this test have not been influenced by sources from within Cooper Lighting Solutions or from external interests.



**Test Information**

Test Method: LM-79-08  
Report Number: P493204  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2011-037-40)  
Test Lab: INNOVATION CENTER  
Issue Date: 3/8/2021  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LDA2B059030R45D010 2LBD1WH  
Description: 500 LUMEN 2IN ADJUSTABLE LED LUMINAIRE WITH 90 CRI LEDS AND 3000K CCT LEDS  
Light Source: -  
Ballast/Driver: -

Luminaire Equipment: Sample No.    Condition    Description

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 648.3 lumens  
Efficiency: N/A  
Efficacy: 92.6 lumens/watt  
Spacing Criteria (0/90/45): 0.71 / 0.71 / 0.65  
Luminous Opening: Circular (Dia: 0.17' x H: 0')  
CIE Type: Direct

Input Watts (W): 7  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT

TEST NUMBER: P493204

CATALOG NUMBER: LDA2B059030R45D010 2LBD1WH

### Luminous Intensity Polar Plot





TEST NUMBER: P493204

CATALOG NUMBER: LDA2B059030R45D010 2LBD1WH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	114	112	110	108	112	110	108	106	106	104	103		102	101	100		99	98	97	95
2	110	106	102	99	108	104	101	98	101	98	96		98	96	94		95	94	92	91
3	105	100	96	93	104	99	95	92	96	93	90		94	91	89		92	90	88	86
4	101	95	90	87	100	94	90	86	92	88	85		90	87	84		88	86	84	82
5	97	90	86	82	96	90	85	82	88	84	81		86	83	80		85	82	80	78
6	94	86	81	78	92	86	81	77	84	80	77		83	79	76		82	78	76	75
7	90	82	77	74	89	82	77	74	81	76	73		80	76	73		78	75	73	71
8	87	79	74	71	86	78	74	70	77	73	70		76	73	70		76	72	70	68
9	84	76	71	67	83	75	70	67	74	70	67		73	70	67		73	69	67	66
10	81	73	68	65	80	72	68	64	71	67	64		71	67	64		70	67	64	63

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	643442
5°	633618
10°	591298
15°	516027
20°	394556
25°	229123
30°	97188
35°	40233
40°	17775
45°	9210
50°	4605
55°	1118
60°	592
65°	350
70°	433
75°	0
80°	0
85°	0



TEST NUMBER: P493204

CATALOG NUMBER: LDA2B059030R45D010 2LBD1WH

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	119.1	18.4
10°-20°	275.5	42.5
20°-30°	192.6	29.7
30°-40°	47.7	7.4
40°-50°	11.1	1.7
50°-60°	1.8	0.3
60°-70°	0.3	0.1
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	587.3	90.6
0°-40°	635.0	97.9
0°-60°	647.8	99.9
0°-90°	648.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	648.3	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	1304	
5°	1279	119
15°	1010	276
25°	421	193
35°	67	48
45°	13	11
55°	1	2
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P493204

CATALOG NUMBER: LDA2B059030R45D010 2LBD1WH

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	1304.2
1°	1301.4
2°	1300.7
3°	1296.6
4°	1285.0
5°	1279.4
6°	1267.8
7°	1251.2
8°	1230.8
9°	1209.8
10°	1180.3
11°	1156.1
12°	1126.6
13°	1088.4
14°	1049.5
15°	1010.3
16°	967.0
17°	915.6
18°	863.5
19°	809.9
20°	751.5
21°	681.6
22.5°	590.9
23°	553.6
24°	486.5
25°	420.9
26°	359.4
27°	302.0
28°	251.6
29°	207.6
30°	170.6
32.5°	105.1
35°	66.8
37.5°	43.3
40°	27.6
42.5°	18.8
45°	13.2
47.5°	9.4
50°	6.0
52.5°	3.1
55°	1.3
57.5°	0.6
60°	0.6
62.5°	0.3
65°	0.3



TEST NUMBER: P493204

CATALOG NUMBER: LDA2B059030R45D010 2LBD1WH

**CANDELA DISTRIBUTION (continued):**

	0°
67.5°	0.3
70°	0.3
72.5°	0.3
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)