

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P493283

Luminaire Tested: **LDA2B059030R70D010 2LBDL1WH**

Issue Date: 3/9/2021

This test was performed under the Supervised Manufacturer's Testing Program. The results of this test have not been influenced by sources from within Cooper Lighting Solutions or from external interests.



Test Information

Test Method: LM-79-08
Report Number: P493283
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2011-037-81)
Test Lab: INNOVATION CENTER
Issue Date: 3/9/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LDA2B059030R70D010 2LBDL1WH
Description: 500 LUMEN 2IN ADJUSTABLE LED LUMINAIRE WITH 90 CRI LEDS AND 3000K CCT LEDS
Light Source: -
Ballast/Driver: -

Luminaire Equipment: Sample No. Condition Description

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 569.5 lumens
Efficiency: N/A
Efficacy: 81.4 lumens/watt
Spacing Criteria (0/90/45): 1.12 / 1.12 / 1.06
Luminous Opening: Circular (Dia: 0.17' x H: 0')
CIE Type: Direct

Input Watts (W): 7
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P493283

CATALOG NUMBER: LDA2B059030R70D010 2LBDL1WH

Luminous Intensity Polar Plot





TEST NUMBER: P493283

CATALOG NUMBER: LDA2B059030R70D010 2LBDL1WH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	113	110	108	105	111	108	106	103	104	102	100		100	99	97		97	96	94	93
2	107	102	97	94	105	100	96	93	97	93	91		94	91	89		91	89	87	85
3	101	94	89	84	99	93	88	84	90	86	82		87	84	81		85	82	80	78
4	95	87	81	76	93	86	80	76	84	79	75		82	77	74		80	76	73	72
5	90	81	74	70	88	80	74	69	78	73	69		76	72	68		74	71	67	66
6	85	75	68	64	83	74	68	63	72	67	63		71	66	63		70	65	62	61
7	80	70	63	59	78	69	63	58	68	62	58		66	61	58		65	61	57	56
8	75	65	58	54	74	64	58	54	63	58	54		62	57	53		61	57	53	52
9	71	61	54	50	70	60	54	50	59	54	50		58	53	50		57	53	49	48
10	68	57	51	46	66	57	50	46	56	50	46		55	50	46		54	49	46	45

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	225466
5°	224148
10°	222632
15°	218506
20°	210640
25°	201633
30°	192098
35°	158521
40°	103046
45°	53864
50°	25022
55°	9204
60°	888
65°	700
70°	433
75°	572
80°	0
85°	0



TEST NUMBER: P493283

CATALOG NUMBER: LDA2B059030R70D010 2LBDL1WH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	42.8	7.5
10°-20°	120.2	21.1
20°-30°	170.6	30.0
30°-40°	159.6	28.0
40°-50°	64.2	11.3
50°-60°	11.2	2.0
60°-70°	0.5	0.1
70°-80°	0.3	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	333.7	58.6
0°-40°	493.2	86.6
0°-60°	568.7	99.9
0°-90°	569.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	569.5	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	457	
5°	453	43
15°	428	120
25°	370	171
35°	263	160
45°	77	64
55°	11	11
65°	1	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P493283

CATALOG NUMBER: LDA2B059030R70D010 2LBDL1WH

CANDELA DISTRIBUTION (FULL):

0°	
0°	457.0
1°	457.6
2°	456.7
3°	454.8
4°	453.9
5°	452.6
6°	447.6
7°	449.2
8°	444.8
9°	443.8
10°	444.4
11°	440.4
12°	439.4
13°	434.4
14°	432.5
15°	427.8
16°	425.0
17°	419.4
18°	412.8
19°	409.0
20°	401.2
21°	395.2
22.5°	384.2
23°	381.4
24°	376.1
25°	370.4
26°	366.0
27°	359.8
28°	353.5
29°	346.0
30°	337.2
32.5°	306.4
35°	263.2
37.5°	212.0
40°	160.0
42.5°	114.2
45°	77.2
47.5°	50.8
50°	32.6
52.5°	20.4
55°	10.7
57.5°	3.5
60°	0.9
62.5°	0.6
65°	0.6



TEST NUMBER: P493283

CATALOG NUMBER: LDA2B059030R70D010 2LBDL1WH

CANDELA DISTRIBUTION (continued):

	0°
67.5°	0.3
70°	0.3
72.5°	0.3
75°	0.3
77.5°	0.3
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)