

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P279306

Luminaire Tested: **LDA2B059027D010 EU2B05FL409027 2LBALD1LI**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P279306
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-1811-033-3)
Test Lab: INNOVATION CENTER(G2)
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LDA2B059027D010 EU2B05FL409027 2LBALD1LI
Description: PORTFOLIO 2IN ADJ 500 LUMEN LED LUMINAIRE WITH FLOOD OPTIC AND 2in
ADJ spun Refl w/lens Self-Flanged, H
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 658.7 lumens
Efficiency: N/A
Efficacy: 94.1 lumens/watt
Spacing Criteria (0/90/45): 0.61 / 0.61 / 0.55
Luminous Opening: Circular (Dia: 0.17' x H: 0')
CIE Type: Direct


Input Watts (W): 7
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P279306

CATALOG NUMBER: LDA2B059027D010 EU2B05FL409027 2LBALD1LI

Luminous Intensity Polar Plot





TEST NUMBER: P279306

CATALOG NUMBER: LDA2B059027D010 EU2B05FL409027 2LBALD1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									20																	
RC	80									70									50									30									10									0								
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																								
RCR																																																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																																				
1	115	113	111	109	112	110	109	107	106	105	104	103	102	101	99	99	98	96																																				
2	111	107	104	101	109	105	102	100	102	100	98	99	97	96	97	95	94	92																																				
3	107	102	98	95	105	101	97	94	98	95	93	96	94	92	94	92	90	89																																				
4	103	98	93	90	102	97	93	90	95	91	89	93	90	88	91	89	87	85																																				
5	100	94	89	86	98	93	89	86	91	88	85	90	87	84	88	86	83	82																																				
6	97	90	85	82	95	89	85	82	88	84	82	87	83	81	85	83	80	79																																				
7	94	87	82	79	92	86	82	79	85	81	78	84	81	78	83	80	78	77																																				
8	91	84	79	76	90	83	79	76	82	78	76	81	78	75	80	77	75	74																																				
9	88	81	76	73	87	80	76	73	79	76	73	79	75	73	78	75	73	72																																				
10	85	78	74	71	84	78	74	71	77	73	71	76	73	70	76	72	70	69																																				

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	905763
5°	886590
10°	808069
15°	631255
20°	373713
25°	138922
30°	43410
35°	19333
40°	8952
45°	4186
50°	2303
55°	1290
60°	592
65°	350
70°	433
75°	0
80°	0
85°	0



TEST NUMBER: P279306

CATALOG NUMBER: LDA2B059027D010 EU2B05FL409027 2LBALD1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	165.5	25.1
10°-20°	329.1	50.0
20°-30°	134.8	20.5
30°-40°	22.3	3.4
40°-50°	5.3	0.8
50°-60°	1.4	0.2
60°-70°	0.3	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	629.3	95.5
0°-40°	651.7	98.9
0°-60°	658.3	99.9
0°-90°	658.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	658.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1836	
5°	1790	165
15°	1236	329
25°	255	135
35°	32	22
45°	6	5
55°	2	1
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P279306

CATALOG NUMBER: LDA2B059027D010 EU2B05FL409027 2LBALD1LI

CANDELA DISTRIBUTION (FULL):

	0°
0°	1835.9
1°	1829.5
2°	1821.0
3°	1813.5
4°	1803.5
5°	1790.2
6°	1770.5
7°	1744.8
8°	1708.2
9°	1663.8
10°	1613.0
11°	1554.0
12°	1487.5
13°	1411.6
14°	1327.2
15°	1235.9
17.5°	980.1
20°	711.8
22.5°	455.7
25°	255.2
27.5°	134.6
30°	76.2
32.5°	48.4
35°	32.1
37.5°	21.2
40°	13.9
42.5°	9.1
45°	6.0
47.5°	4.2
50°	3.0
52.5°	2.1
55°	1.5
57.5°	0.9
60°	0.6
62.5°	0.3
65°	0.3
67.5°	0.3
70°	0.3
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0



TEST NUMBER: P279306

CATALOG NUMBER: LDA2B059027D010 EU2B05FL409027 2LBALD1LI

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







85°		0.0
87.5°		0.0



(END OF REPORT)