

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P279321

Luminaire Tested: **LDA2B059030D010 EU2B05FL409030 2LBAD1GPH**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P279321
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-1811-033-3)
Test Lab: INNOVATION CENTER(G2)
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LDA2B059030D010 EU2B05FL409030 2LBAD1GPH
Description: PORTFOLIO 2IN ADJ 500 LUMEN LED LUMINAIRE WITH FLOOD OPTIC AND 2in
ADJ spun Refl, Self-Flanged, GPH
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 681.2 lumens
Efficiency: N/A
Efficacy: 97.3 lumens/watt
Spacing Criteria (0/90/45): 0.61 / 0.61 / 0.55
Luminous Opening: Circular (Dia: 0.17' x H: 0')
CIE Type: Direct


Input Watts (W): 7
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P279321

CATALOG NUMBER: LDA2B059030D010 EU2B05FL409030 2LBAD1GPH

Luminous Intensity Polar Plot





TEST NUMBER: P279321

CATALOG NUMBER: LDA2B059030D010 EU2B05FL409030 2LBAD1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0													
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100						100													
1	115	113	111	109	112	110	109	107	106	105	104	103	102	101	99	99	98	96						96													
2	111	107	104	101	109	105	102	100	102	100	98	99	97	96	97	95	94	92						92													
3	107	102	98	95	105	101	97	94	98	95	93	96	94	92	94	92	90	89						89													
4	103	98	93	90	102	97	93	90	95	91	89	93	90	88	91	89	87	85						85													
5	100	94	89	86	98	93	89	86	91	88	85	90	87	84	88	86	83	82						82													
6	97	90	85	82	95	89	85	82	88	84	82	87	83	81	85	83	80	79						79													
7	94	87	82	79	92	86	82	79	85	81	78	84	81	78	83	80	78	77						77													
8	91	84	79	76	90	83	79	76	82	78	76	81	78	75	80	77	75	74						74													
9	88	81	76	73	87	80	76	73	79	76	73	79	75	73	78	75	73	72						72													
10	85	78	74	71	84	78	74	71	77	73	71	76	73	70	76	72	70	69						69													

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	936647
5°	916850
10°	835622
15°	652810
20°	386471
25°	143658
30°	44891
35°	19936
40°	9274
45°	4396
50°	2379
55°	1376
60°	592
65°	350
70°	433
75°	0
80°	0
85°	0



TEST NUMBER: P279321

CATALOG NUMBER: LDA2B059030D010 EU2B05FL409030 2LBAD1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	171.1	25.1
10°-20°	340.3	50.0
20°-30°	139.4	20.5
30°-40°	23.1	3.4
40°-50°	5.5	0.8
50°-60°	1.4	0.2
60°-70°	0.3	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	650.8	95.5
0°-40°	673.9	98.9
0°-60°	680.8	99.9
0°-90°	681.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	681.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1898	
5°	1851	171
15°	1278	340
25°	264	139
35°	33	23
45°	6	5
55°	2	1
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P279321

CATALOG NUMBER: LDA2B059030D010 EU2B05FL409030 2LBAD1GPH

CANDELA DISTRIBUTION (FULL):

	0°
0°	1898.5
1°	1891.9
2°	1883.2
3°	1875.4
4°	1865.0
5°	1851.3
6°	1830.9
7°	1804.4
8°	1766.5
9°	1720.6
10°	1668.0
11°	1607.0
12°	1538.2
13°	1459.8
14°	1372.5
15°	1278.1
17.5°	1013.5
20°	736.1
22.5°	471.3
25°	263.9
27.5°	139.2
30°	78.8
32.5°	50.0
35°	33.1
37.5°	21.9
40°	14.4
42.5°	9.4
45°	6.3
47.5°	4.4
50°	3.1
52.5°	2.2
55°	1.6
57.5°	0.9
60°	0.6
62.5°	0.3
65°	0.3
67.5°	0.3
70°	0.3
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0



TEST NUMBER: P279321

CATALOG NUMBER: LDA2B059030D010 EU2B05FL409030 2LBAD1GPH

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







85°		0.0
87.5°		0.0



(END OF REPORT)