

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P494262

Luminaire Tested: **LDA2B059730R35D010 2LBDL1H**

Issue Date: 3/9/2021

This test was performed under the Supervised Manufacturer's Testing Program. The results of this test have not been influenced by sources from within Cooper Lighting Solutions or from external interests.



**Test Information**

Test Method: LM-79-08  
Report Number: P494262  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2011-037-29)  
Test Lab: INNOVATION CENTER  
Issue Date: 3/9/2021  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LDA2B059730R35D010 2LBDL1H  
Description: 500 LUMEN 2IN ADJUSTABLE LED LUMINAIRE WITH 97 CRI LEDS AND 3000K CCT LEDS  
Light Source: -  
Ballast/Driver: -

Luminaire Equipment: Sample No.    Condition    Description


**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 550.2 lumens  
Efficiency: N/A  
Efficacy: 78.6 lumens/watt  
Spacing Criteria (0/90/45): 0.54 / 0.54 / 0.51  
Luminous Opening: Circular (Dia: 0.17' x H: 0')  
CIE Type: Direct

Input Watts (W): 7  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT

TEST NUMBER: P494262  
CATALOG NUMBER: LDA2B059730R35D010 2LBDL1H

### Luminous Intensity Polar Plot





TEST NUMBER: P494262

CATALOG NUMBER: LDA2B059730R35D010 2LBDL1H

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	115	113	111	109	112	110	109	107	106	105	104	103	102	101	99	99	98	96
2	111	107	104	101	109	105	102	100	102	100	98	99	97	96	97	95	94	92
3	107	102	98	95	105	101	97	94	98	95	93	96	93	91	94	92	90	89
4	103	97	93	90	102	96	92	89	94	91	88	92	90	87	91	88	87	85
5	100	93	89	86	98	93	88	85	91	87	85	89	86	84	88	85	83	82
6	96	90	85	82	95	89	85	82	88	84	81	86	83	81	85	82	80	79
7	93	86	82	79	92	86	82	79	85	81	78	84	80	78	83	80	77	76
8	90	83	79	76	89	83	79	76	82	78	75	81	78	75	80	77	75	74
9	88	81	76	73	87	80	76	73	79	76	73	79	75	73	78	75	72	71
10	85	78	74	71	84	78	73	71	77	73	70	76	73	70	76	72	70	69

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	839751
5°	811857
10°	709478
15°	496005
20°	260412
25°	111921
30°	51158
35°	24814
40°	12623
45°	6419
50°	3531
55°	1462
60°	592
65°	350
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P494262

CATALOG NUMBER: LDA2B059730R35D010 2LBDL1H

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	149.4	27.2
10°-20°	259.1	47.1
20°-30°	103.4	18.8
30°-40°	28.2	5.1
40°-50°	7.8	1.4
50°-60°	1.8	0.3
60°-70°	0.4	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	512.0	93.1
0°-40°	540.2	98.2
0°-60°	549.8	99.9
0°-90°	550.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	550.2	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	1702	
5°	1639	149
15°	971	259
25°	206	103
35°	41	28
45°	9	8
55°	2	2
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P494262

CATALOG NUMBER: LDA2B059730R35D010 2LBDL1H

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	1702.1
1°	1694.9
2°	1688.0
3°	1677.6
4°	1662.0
5°	1639.3
6°	1609.6
7°	1572.8
8°	1530.8
9°	1472.6
10°	1416.2
11°	1346.2
12°	1256.7
13°	1166.6
14°	1074.7
15°	971.1
16°	869.2
17°	764.4
18°	670.2
19°	581.3
20°	496.0
21°	417.7
22.5°	323.9
23°	293.7
24°	246.4
25°	205.6
26°	173.0
27°	144.5
28°	122.4
29°	104.2
30°	89.8
32.5°	60.2
35°	41.2
37.5°	28.8
40°	19.6
42.5°	13.2
45°	9.2
47.5°	6.6
50°	4.6
52.5°	3.2
55°	1.7
57.5°	0.9
60°	0.6
62.5°	0.6
65°	0.3



TEST NUMBER: P494262

CATALOG NUMBER: LDA2B059730R35D010 2LBDL1H

**CANDELA DISTRIBUTION (continued):**

	0°
67.5°	0.3
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)