

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P742610

Luminaire Tested: LD4D10D010-EU4DR600210IC9035-4LBDP1MW

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P742610
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-57)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D10D010-EU4DR600210IC9035-4LBDP1MW
Description: 4 INCH ROUND DEEP 45° CUTOFF MATTE WHITE TRIM, WITH 60° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3500K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 958.1 lumens
Efficiency: N/A
Efficacy: 81.9 lumens/watt
Spacing Criteria (0/90/45): 0.91 / 0.91 / 0.83
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 11.7
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P742610

CATALOG NUMBER: LD4D10D010-EU4DR600210IC9035-4LBDP1MW

Luminous Intensity Polar Plot





TEST NUMBER: P742610

CATALOG NUMBER: LD4D10D010-EU4DR600210IC9035-4LBDP1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	113	110	108	105	111	108	106	104	104	102	100	100	99	97	97	96	95	93																			
2	107	102	98	95	105	101	97	94	97	94	92	94	92	90	92	90	88	86																			
3	102	96	90	86	100	94	89	86	91	88	84	89	86	83	87	84	82	80																			
4	97	89	84	80	95	88	83	79	86	82	78	84	80	77	82	79	76	75																			
5	92	84	78	74	91	83	78	74	81	77	73	80	76	72	78	75	72	70																			
6	88	79	73	69	87	78	73	69	77	72	68	75	71	68	74	70	67	66																			
7	84	75	69	65	83	74	68	64	73	68	64	72	67	64	71	67	63	62																			
8	80	71	65	61	79	70	65	61	69	64	60	68	64	60	67	63	60	59																			
9	77	67	61	57	75	67	61	57	66	61	57	65	60	57	64	60	57	55																			
10	73	64	58	54	72	63	58	54	62	58	54	62	57	54	61	57	54	53																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	124328
5°	127380
10°	128931
15°	122820
20°	108285
25°	87584
30°	59246
35°	29691
40°	4807
45°	4713
50°	4810
55°	4877
60°	5026
65°	5119
70°	5239
75°	5319
80°	5097
85°	4262

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 75°
 Luminance: 5319 cd/sqm



TEST NUMBER: P742610

CATALOG NUMBER: LD4D10D010-EU4DR600210IC9035-4LBDP1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	111.0	11.6
10°-20°	300.3	31.3
20°-30°	323.1	33.7
30°-40°	140.5	14.7
40°-50°	23.6	2.5
50°-60°	22.9	2.4
60°-70°	19.6	2.0
70°-80°	13.1	1.4
80°-90°	3.9	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	734.5	76.7
0°-40°	874.9	91.3
0°-60°	921.4	96.2
0°-90°	958.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	958.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1138	
5°	1161	111
15°	1086	300
25°	726	323
35°	223	140
45°	30	24
55°	26	23
65°	20	20
75°	13	13
85°	3	4
90°	0	



TEST NUMBER: P742610

CATALOG NUMBER: LD4D10D010-EU4DR600210IC9035-4LBDP1MW

CANDELA DISTRIBUTION (FULL):

0°	
0°	1137.9
2.5°	1169.9
5°	1161.4
7.5°	1164.1
10°	1162.1
12.5°	1138.1
15°	1085.8
17.5°	1015.6
20°	931.3
22.5°	841.1
25°	726.5
27.5°	581.1
30°	469.6
32.5°	361.9
35°	222.6
37.5°	95.2
40°	33.7
42.5°	31.1
45°	30.5
47.5°	29.4
50°	28.3
52.5°	26.9
55°	25.6
57.5°	24.3
60°	23.0
62.5°	21.5
65°	19.8
67.5°	18.2
70°	16.4
72.5°	14.5
75°	12.6
77.5°	10.4
80°	8.1
82.5°	5.8
85°	3.4
87.5°	1.2
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)