

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P743723

Luminaire Tested: LD4D15D010-EU4DR700215IC9027-4LBDP1B

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P743723
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-73)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D15D010-EU4DR700215IC9027-4LBDP1B
Description: 4 INCH ROUND DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 70° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 763.8 lumens
Efficiency: N/A
Efficacy: 48.3 lumens/watt
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.82
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 15.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P743723

CATALOG NUMBER: LD4D15D010-EU4DR700215IC9027-4LBDP1B

Luminous Intensity Polar Plot





TEST NUMBER: P743723

CATALOG NUMBER: LD4D15D010-EU4DR700215IC9027-4LBDP1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	112	109	106	103	110	107	104	102	103	101	99	99	97	96	95	94	93	91																			
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	85	83																			
3	100	92	87	82	98	91	86	81	88	84	80	86	82	79	83	80	78	76																			
4	94	86	80	75	92	85	79	74	82	77	73	80	76	73	78	75	72	70																			
5	89	80	74	69	87	79	73	69	77	72	68	75	71	67	74	70	67	65																			
6	85	75	68	64	83	74	68	64	73	67	63	71	66	63	70	66	62	61																			
7	80	70	64	59	79	70	64	59	68	63	59	67	62	59	66	62	58	57																			
8	77	66	60	56	75	66	60	56	65	59	55	64	59	55	63	58	55	53																			
9	73	63	57	52	72	62	56	52	61	56	52	60	55	52	60	55	52	50																			
10	70	59	53	49	69	59	53	49	58	53	49	57	52	49	57	52	49	48																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	93822
5°	91033
10°	88502
15°	87336
20°	81554
25°	61267
30°	43312
35°	15339
40°	8073
45°	8591
50°	8907
55°	9067
60°	9134
65°	8919
70°	8434
75°	7810
80°	6921
85°	5641

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 60°
 Luminance: 9134 cd/sqm



TEST NUMBER: P743723

CATALOG NUMBER: LD4D15D010-EU4DR700215IC9027-4LBDP1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	78.3	10.2
10°-20°	214.7	28.1
20°-30°	236.5	31.0
30°-40°	90.4	11.8
40°-50°	42.7	5.6
50°-60°	42.4	5.6
60°-70°	34.0	4.4
70°-80°	19.5	2.6
80°-90°	5.3	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	529.5	69.3
0°-40°	619.9	81.2
0°-60°	705.0	92.3
0°-90°	763.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	763.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	859	
5°	830	78
15°	772	215
25°	508	237
35°	115	90
45°	56	43
55°	48	42
65°	34	34
75°	18	20
85°	4	5
90°	0	



TEST NUMBER: P743723

CATALOG NUMBER: LD4D15D010-EU4DR700215IC9027-4LBDP1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	858.7
2.5°	849.7
5°	830.0
7.5°	813.6
10°	797.7
12.5°	784.2
15°	772.1
17.5°	742.9
20°	701.4
22.5°	612.0
25°	508.2
27.5°	442.4
30°	343.3
32.5°	221.7
35°	115.0
37.5°	62.1
40°	56.6
42.5°	56.1
45°	55.6
47.5°	54.4
50°	52.4
52.5°	50.0
55°	47.6
57.5°	44.9
60°	41.8
62.5°	38.2
65°	34.5
67.5°	30.5
70°	26.4
72.5°	22.3
75°	18.5
77.5°	14.6
80°	11.0
82.5°	7.7
85°	4.5
87.5°	1.8
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)