

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P736020

Luminaire Tested: LD4D15D010-EU4DR700215IC9035-4LBDP1MW

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P736020
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-73)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D15D010-EU4DR700215IC9035-4LBDP1MW
Description: 4 INCH ROUND DEEP 45° CUTOFF MATTE WHITE TRIM, WITH 70° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3500K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1117.7 lumens
Efficiency: N/A
Efficacy: 70.7 lumens/watt
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.82
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 15.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P736020
CATALOG NUMBER: LD4D15D010-EU4DR700215IC9035-4LBDP1MW

Luminous Intensity Polar Plot





TEST NUMBER: P736020

CATALOG NUMBER: LD4D15D010-EU4DR700215IC9035-4LBDP1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	112	109	106	103	110	107	104	102	103	101	99	99	97	96	95	94	93	91																			
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	85	83																			
3	100	92	87	82	98	91	86	81	88	84	80	86	82	79	83	80	78	76																			
4	94	86	80	75	92	85	79	74	82	77	73	80	76	73	78	75	72	70																			
5	89	80	74	69	87	79	73	69	77	72	68	75	71	67	74	70	67	65																			
6	85	75	68	64	83	74	68	64	73	67	63	71	66	63	70	66	62	61																			
7	80	70	64	59	79	70	64	59	68	63	59	67	62	59	66	62	58	57																			
8	77	66	60	56	75	66	60	56	65	59	55	64	59	55	63	58	55	53																			
9	73	63	57	52	72	62	56	52	61	56	52	60	55	52	60	55	52	50																			
10	70	59	53	49	69	59	53	49	58	53	49	57	52	49	57	52	49	48																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	137308
5°	133226
10°	129508
15°	127809
20°	119342
25°	89657
30°	63385
35°	22448
40°	11810
45°	12578
50°	13020
55°	13258
60°	13352
65°	13056
70°	12331
75°	11398
80°	10130
85°	8274

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 57.5°
 Luminance: 13360 cd/sqm



TEST NUMBER: P736020

CATALOG NUMBER: LD4D15D010-EU4DR700215IC9035-4LBDP1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	114.6	10.3
10°-20°	314.3	28.1
20°-30°	346.1	31.0
30°-40°	132.2	11.8
40°-50°	62.5	5.6
50°-60°	62.1	5.6
60°-70°	49.7	4.4
70°-80°	28.6	2.6
80°-90°	7.8	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	774.9	69.3
0°-40°	907.2	81.2
0°-60°	1031.7	92.3
0°-90°	1117.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1117.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1257	
5°	1215	115
15°	1130	314
25°	744	346
35°	168	132
45°	81	62
55°	70	62
65°	50	50
75°	27	29
85°	7	8
90°	0	



TEST NUMBER: P736020

CATALOG NUMBER: LD4D15D010-EU4DR700215IC9035-4LBDP1MW

CANDELA DISTRIBUTION (FULL):

	0°
0°	1256.7
2.5°	1243.5
5°	1214.7
7.5°	1190.6
10°	1167.3
12.5°	1147.6
15°	1129.9
17.5°	1087.1
20°	1026.4
22.5°	895.5
25°	743.7
27.5°	647.4
30°	502.4
32.5°	324.5
35°	168.3
37.5°	90.9
40°	82.8
42.5°	82.2
45°	81.4
47.5°	79.6
50°	76.6
52.5°	73.2
55°	69.6
57.5°	65.7
60°	61.1
62.5°	55.9
65°	50.5
67.5°	44.6
70°	38.6
72.5°	32.7
75°	27.0
77.5°	21.3
80°	16.1
82.5°	11.3
85°	6.6
87.5°	2.6
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)