

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P744605

Luminaire Tested: LD4D20D010-EU4DR6020359035-4LBDP1LI

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P744605
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-57)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D20D010-EU4DR6020359035-4LBDP1LI
Description: 4 INCH ROUND DEEP 45° CUTOFF SPECULAR CLEAR TRIM, WITH 60° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3500K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2049.8 lumens
Efficiency: N/A
Efficacy: 88.7 lumens/watt
Spacing Criteria (0/90/45): 0.91 / 0.91 / 0.83
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 23.1
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P744605
CATALOG NUMBER: LD4D20D010-EU4DR6020359035-4LBDP1LI

Luminous Intensity Polar Plot





TEST NUMBER: P744605

CATALOG NUMBER: LD4D20D010-EU4DR6020359035-4LBDP1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	113	110	108	105	111	108	106	104	104	102	100	100	99	97	97	96	95	93																			
2	107	102	98	95	105	101	97	94	97	94	92	94	92	90	92	90	88	86																			
3	102	96	90	86	100	94	89	86	91	88	84	89	86	83	87	84	82	80																			
4	97	89	84	80	95	88	83	79	86	82	78	84	80	77	82	79	76	75																			
5	92	84	78	74	91	83	78	74	81	77	73	80	76	72	78	75	72	70																			
6	88	79	73	69	87	78	73	69	77	72	68	75	71	68	74	70	67	66																			
7	84	75	69	65	83	74	68	64	73	68	64	72	67	64	71	67	63	62																			
8	80	71	65	61	79	70	65	61	69	64	60	68	64	60	67	63	60	59																			
9	77	67	61	57	75	67	61	57	66	61	57	65	60	57	64	60	57	55																			
10	73	64	58	54	72	63	58	54	62	58	54	62	57	54	61	57	54	53																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	265984
5°	272517
10°	275812
15°	262744
20°	231662
25°	187368
30°	126744
35°	63517
40°	10298
45°	10090
50°	10284
55°	10439
60°	10729
65°	10988
70°	11245
75°	11356
80°	10948
85°	9151

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 75°
 Luminance: 11356 cd/sqm



TEST NUMBER: P744605

CATALOG NUMBER: LD4D20D010-EU4DR6020359035-4LBDP1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	237.5	11.6
10°-20°	642.5	31.3
20°-30°	691.3	33.7
30°-40°	300.5	14.7
40°-50°	50.5	2.5
50°-60°	49.1	2.4
60°-70°	42.0	2.0
70°-80°	28.1	1.4
80°-90°	8.4	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1571.2	76.7
0°-40°	1871.7	91.3
0°-60°	1971.3	96.2
0°-90°	2049.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2049.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2434	
5°	2485	237
15°	2323	642
25°	1554	691
35°	476	300
45°	65	50
55°	55	49
65°	42	42
75°	27	28
85°	7	8
90°	0	



TEST NUMBER: P744605

CATALOG NUMBER: LD4D20D010-EU4DR6020359035-4LBDP1LI

CANDELA DISTRIBUTION (FULL):

0°	
0°	2434.4
2.5°	2502.8
5°	2484.7
7.5°	2490.4
10°	2486.0
12.5°	2434.6
15°	2322.8
17.5°	2172.6
20°	1992.4
22.5°	1799.5
25°	1554.2
27.5°	1243.1
30°	1004.6
32.5°	774.3
35°	476.2
37.5°	203.7
40°	72.2
42.5°	66.5
45°	65.3
47.5°	63.0
50°	60.5
52.5°	57.6
55°	54.8
57.5°	52.0
60°	49.1
62.5°	46.0
65°	42.5
67.5°	39.0
70°	35.2
72.5°	31.1
75°	26.9
77.5°	22.2
80°	17.4
82.5°	12.4
85°	7.3
87.5°	2.5
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)