

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P739682

Luminaire Tested: LD4D02D010-EU4DR700210IC9024-4LBDP1B

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P739682
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-73)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D02D010-EU4DR700210IC9024-4LBDP1B
Description: 4 INCH ROUND DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 70° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2400K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 178.6 lumens
Efficiency: N/A
Efficacy: 35.0 lumens/watt
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.82
Luminous Opening: Circular (Dia: 0.35' x H: 0')

CIE Type: Direct

Input Watts (W): 5.1
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P739682

CATALOG NUMBER: LD4D02D010-EU4DR700210IC9024-4LBDP1B

Luminous Intensity Polar Plot





TEST NUMBER: P739682

CATALOG NUMBER: LD4D02D010-EU4DR700210IC9024-4LBDP1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	112	109	106	103	110	107	104	102	103	101	99	99	97	96	95	94	93	91																			
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	85	83																			
3	100	92	87	82	98	91	86	81	88	84	80	86	82	79	83	80	78	76																			
4	94	86	80	75	92	85	79	74	82	77	73	80	76	73	78	75	72	70																			
5	89	80	74	69	88	79	73	69	77	72	68	75	71	67	74	70	67	65																			
6	85	75	68	64	83	74	68	64	73	67	63	71	66	63	70	66	62	61																			
7	80	70	64	59	79	70	64	59	68	63	59	67	62	59	66	62	58	57																			
8	77	66	60	56	75	66	60	56	65	59	55	64	59	55	63	58	55	53																			
9	73	63	57	52	72	62	56	52	61	56	52	60	55	52	60	55	52	50																			
10	70	59	53	49	69	59	53	49	58	53	49	57	52	49	57	52	49	48																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	21940
5°	21289
10°	20691
15°	20417
20°	19069
25°	14322
30°	10131
35°	3588
40°	1883
45°	2009
50°	2091
55°	2114
60°	2120
65°	2094
70°	1981
75°	1815
80°	1636
85°	1254

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 57.5°
 Luminance: 2135 cd/sqm



TEST NUMBER: P739682

CATALOG NUMBER: LD4D02D010-EU4DR700210IC9024-4LBDP1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	18.3	10.3
10°-20°	50.2	28.1
20°-30°	55.3	31.0
30°-40°	21.1	11.8
40°-50°	10.0	5.6
50°-60°	9.9	5.6
60°-70°	7.9	4.4
70°-80°	4.6	2.6
80°-90°	1.2	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	123.8	69.3
0°-40°	145.0	81.2
0°-60°	164.8	92.3
0°-90°	178.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	178.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	201	
5°	194	18
15°	180	50
25°	119	55
35°	27	21
45°	13	10
55°	11	10
65°	8	8
75°	4	5
85°	1	1
90°	0	



TEST NUMBER: P739682

CATALOG NUMBER: LD4D02D010-EU4DR700210IC9024-4LBDP1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	200.8
2.5°	198.6
5°	194.1
7.5°	190.2
10°	186.5
12.5°	183.3
15°	180.5
17.5°	173.7
20°	164.0
22.5°	143.1
25°	118.8
27.5°	103.4
30°	80.3
32.5°	51.9
35°	26.9
37.5°	14.6
40°	13.2
42.5°	13.1
45°	13.0
47.5°	12.7
50°	12.3
52.5°	11.7
55°	11.1
57.5°	10.5
60°	9.7
62.5°	8.9
65°	8.1
67.5°	7.1
70°	6.2
72.5°	5.2
75°	4.3
77.5°	3.4
80°	2.6
82.5°	1.8
85°	1.0
87.5°	0.4
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)