

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P738922

Luminaire Tested: LD4D02D010-EU4DR200210IC9027-4LBS1MW

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P738922
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2310-195-36)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D02D010-EU4DR200210IC9027-4LBS1MW
Description: 4 INCH ROUND SHALLOW MATTE WHITE TRIM, WITH 20° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 357.7 lumens
Efficiency: N/A
Efficacy: 70.1 lumens/watt
Spacing Criteria (0/90/45): 0.34 / 0.34 / 0.36
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 5.1
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P738922

CATALOG NUMBER: LD4D02D010-EU4DR200210IC9027-4LBS1MW

Luminous Intensity Polar Plot





TEST NUMBER: P738922

CATALOG NUMBER: LD4D02D010-EU4DR200210IC9027-4LBS1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10		0		
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	115	113	111	109	113	111	109	108	107	106	104	103	102	101	100	99	98	97			
2	111	108	105	102	109	106	104	101	103	101	99	100	99	97	98	96	95	94			
3	108	103	100	97	106	102	99	96	100	97	95	97	95	93	95	93	92	91			
4	105	99	96	93	103	98	95	92	96	93	91	95	92	90	93	91	89	88			
5	102	96	92	89	100	95	91	89	94	90	88	92	89	87	91	88	86	85			
6	99	93	89	86	98	92	88	86	91	87	85	90	87	84	88	86	84	83			
7	96	90	86	83	95	89	86	83	88	85	82	87	84	82	86	84	82	81			
8	94	87	83	81	93	87	83	80	86	83	80	85	82	80	84	82	80	79			
9	91	85	81	78	91	85	81	78	84	80	78	83	80	78	82	80	78	77			
10	89	83	79	76	88	82	79	76	82	78	76	81	78	76	81	78	76	75			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	222422
5°	200667
10°	112633
15°	57248
20°	24243
25°	11188
30°	5930
35°	3188
40°	1712
45°	1004
50°	578
55°	305
60°	197
65°	129
70°	64
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 1004 cd/sqm



TEST NUMBER: P738922

CATALOG NUMBER: LD4D02D010-EU4DR200210IC9027-4LBS1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	144.9	40.5
10°-20°	142.7	39.9
20°-30°	46.6	13.0
30°-40°	15.9	4.4
40°-50°	5.3	1.5
50°-60°	1.6	0.4
60°-70°	0.5	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	334.3	93.5
0°-40°	350.2	97.9
0°-60°	357.1	99.8
0°-90°	357.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	357.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2036	
5°	1830	145
15°	506	143
25°	93	47
35°	24	16
45°	6	5
55°	2	2
65°	0	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P738922
CATALOG NUMBER: LD4D02D010-EU4DR200210IC9027-4LBS1MW

CANDELA DISTRIBUTION (FULL):

	0°
0°	2035.7
0.5°	2035.7
1°	2033.2
1.5°	2028.1
2°	2018.9
2.5°	2006.6
3°	1989.2
3.5°	1964.9
4°	1928.8
4.5°	1884.9
5°	1829.6
5.5°	1756.9
6°	1682.4
6.5°	1597.1
7°	1513.5
7.5°	1415.6
8°	1328.2
8.5°	1240.3
9°	1159.1
9.5°	1084.6
10°	1015.2
12.5°	728.9
15°	506.1
17.5°	330.6
20°	208.5
22.5°	135.1
25°	92.8
27.5°	65.3
30°	47.0
32.5°	33.7
35°	23.9
37.5°	16.7
40°	12.0
42.5°	8.7
45°	6.5
47.5°	5.1
50°	3.4
52.5°	2.2
55°	1.6
57.5°	1.3
60°	0.9
62.5°	0.7
65°	0.5



TEST NUMBER: P738922

CATALOG NUMBER: LD4D02D010-EU4DR200210IC9027-4LBS1MW

CANDELA DISTRIBUTION (continued):

	0°
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report





— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



67.5°		0.4
70°		0.2

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)