

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P745630

Luminaire Tested: LD4D25D010-EU4DR6520359040-4LBDP1B

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P745630
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-59)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D25D010-EU4DR6520359040-4LBDP1B
Description: 4 INCH ROUND DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 4000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1687.2 lumens
Efficiency: N/A
Efficacy: 67.2 lumens/watt
Spacing Criteria (0/90/45): 0.98 / 0.98 / 0.92
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 25.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P745630
CATALOG NUMBER: LD4D25D010-EU4DR6520359040-4LBDP1B

Luminous Intensity Polar Plot





TEST NUMBER: P745630

CATALOG NUMBER: LD4D25D010-EU4DR6520359040-4LBDP1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	113	111	108	106	111	108	106	104	104	103	101	101	99	98	97	96	95	93																			
2	108	103	99	95	106	101	97	94	98	95	92	95	92	90	92	90	88	87																			
3	102	96	91	87	100	94	90	86	92	88	85	89	86	83	87	84	82	80																			
4	97	89	84	79	95	88	83	79	86	82	78	84	80	77	82	79	76	75																			
5	92	83	78	73	90	83	77	73	81	76	72	79	75	72	77	74	71	69																			
6	87	78	72	68	86	77	72	68	76	71	67	74	70	67	73	69	66	65																			
7	83	73	67	63	81	73	67	63	71	66	62	70	66	62	69	65	62	60																			
8	79	69	63	59	77	68	63	59	67	62	58	66	62	58	65	61	58	57																			
9	75	65	59	55	74	65	59	55	64	58	55	63	58	55	62	58	54	53																			
10	71	61	56	52	70	61	55	52	60	55	51	59	55	51	59	54	51	50																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	181504
5°	181660
10°	188054
15°	188359
20°	173421
25°	147765
30°	113118
35°	79910
40°	47168
45°	19145
50°	6952
55°	3867
60°	2207
65°	1215
70°	1278
75°	971
80°	1070
85°	878

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 19145 cd/sqm



TEST NUMBER: P745630

CATALOG NUMBER: LD4D25D010-EU4DR6520359040-4LBDP1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	160.0	9.5
10°-20°	461.4	27.3
20°-30°	553.6	32.8
30°-40°	372.0	22.1
40°-50°	111.4	6.6
50°-60°	19.6	1.2
60°-70°	5.6	0.3
70°-80°	2.7	0.2
80°-90°	0.9	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1175.0	69.6
0°-40°	1547.0	91.7
0°-60°	1678.0	99.5
0°-90°	1687.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1687.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1661	
5°	1656	160
15°	1665	461
25°	1226	554
35°	599	372
45°	124	111
55°	20	20
65°	5	6
75°	2	3
85°	1	1
90°	0	



TEST NUMBER: P745630

CATALOG NUMBER: LD4D25D010-EU4DR6520359040-4LBDP1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	1661.2
2.5°	1668.3
5°	1656.3
7.5°	1681.3
10°	1695.0
12.5°	1691.7
15°	1665.2
17.5°	1600.5
20°	1491.5
22.5°	1363.0
25°	1225.7
27.5°	1070.6
30°	896.6
32.5°	738.9
35°	599.1
37.5°	461.1
40°	330.7
42.5°	216.0
45°	123.9
47.5°	65.6
50°	40.9
52.5°	28.3
55°	20.3
57.5°	14.6
60°	10.1
62.5°	6.6
65°	4.7
67.5°	4.2
70°	4.0
72.5°	3.1
75°	2.3
77.5°	2.1
80°	1.7
82.5°	1.2
85°	0.7
87.5°	0.5
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)