

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P748205

Luminaire Tested: LD4D40BD010-EU4DR7040509040-4LBDP1H

Issue Date: 2/5/2024

**Test Information**

Test Method: LM-79-2019  
Report Number: P748205  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-73)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 2/5/2024  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: PORTFOLIO  
Catalog Number: LD4D40BD010-EU4DR7040509040-4LBDP1H  
Description: 4 INCH ROUND DEEP 45° CUTOFF SEMI-SPECULAR CLEAR TRIM, WITH 70° OPTIC  
Light Source: (1) HIGH LUMEN LED 90CRI / 4000K CCT  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 4016.8 lumens  
Efficiency: N/A  
Efficacy: 114.1 lumens/watt  
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.82  
Luminous Opening: Circular (Dia: 0.35' x H: 0')  
CIE Type: Direct


Input Watts (W): 35.2  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT



Downlight

TEST NUMBER: P748205  
CATALOG NUMBER: LD4D40BD010-EU4DR7040509040-4LBDP1H

### Luminous Intensity Polar Plot





TEST NUMBER: P748205

CATALOG NUMBER: LD4D40BD010-EU4DR7040509040-4LBDP1H

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	112	109	106	103	110	107	104	102	103	101	99	99	97	96	95	94	93	91																			
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	85	83																			
3	100	92	87	82	98	91	86	81	88	84	80	86	82	79	83	80	78	76																			
4	94	86	80	75	92	85	79	74	82	77	73	80	76	73	78	75	72	70																			
5	89	80	74	69	87	79	73	69	77	72	68	75	71	67	74	70	67	65																			
6	85	75	68	64	83	74	68	64	73	67	63	71	66	63	70	66	62	61																			
7	80	70	64	59	79	70	64	59	68	63	59	67	62	59	66	62	58	57																			
8	77	66	60	56	75	66	60	56	65	59	55	64	59	55	63	58	55	53																			
9	73	63	57	52	72	62	56	52	61	56	52	60	55	52	60	55	52	50																			
10	70	59	53	49	69	59	53	49	58	53	49	57	52	49	57	52	49	48																			

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	493422
5°	478756
10°	465409
15°	459304
20°	428896
25°	322210
30°	227775
35°	80683
40°	42418
45°	45181
50°	46795
55°	47680
60°	47965
65°	46950
70°	44309
75°	41033
80°	36431
85°	29586

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 57.5°  
 Luminance: 47991 cd/sqm



TEST NUMBER: P748205

CATALOG NUMBER: LD4D40BD010-EU4DR7040509040-4LBDP1H

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	411.7	10.3
10°-20°	1129.3	28.1
20°-30°	1243.8	31.0
30°-40°	475.2	11.8
40°-50°	224.4	5.6
50°-60°	223.1	5.6
60°-70°	178.6	4.4
70°-80°	102.6	2.6
80°-90°	27.9	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2784.9	69.3
0°-40°	3260.1	81.2
0°-60°	3707.6	92.3
0°-90°	4016.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4016.8	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	4516	
5°	4365	412
15°	4060	1129
25°	2673	1244
35°	605	475
45°	292	224
55°	250	223
65°	182	179
75°	97	103
85°	24	28
90°	0	



TEST NUMBER: P748205

CATALOG NUMBER: LD4D40BD010-EU4DR7040509040-4LBDP1H

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	4516.0
2.5°	4468.8
5°	4365.1
7.5°	4278.6
10°	4194.9
12.5°	4124.2
15°	4060.5
17.5°	3906.8
20°	3688.7
22.5°	3218.2
25°	2672.7
27.5°	2326.6
30°	1805.4
32.5°	1166.2
35°	604.9
37.5°	326.8
40°	297.4
42.5°	295.3
45°	292.4
47.5°	286.0
50°	275.3
52.5°	263.1
55°	250.3
57.5°	236.0
60°	219.5
62.5°	200.9
65°	181.6
67.5°	160.2
70°	138.7
72.5°	117.3
75°	97.2
77.5°	76.5
80°	57.9
82.5°	40.8
85°	23.6
87.5°	9.3
90°	0.0

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report





Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)