

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P749679

Luminaire Tested: LD4D50D010-EU4DR6540509035-4LBS1LI

Issue Date: 2/2/2024

**Test Information**

Test Method: LM-79-2019  
Report Number: P749679  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-147)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 2/2/2024  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: PORTFOLIO  
Catalog Number: LD4D50D010-EU4DR6540509035-4LBS1LI  
Description: 4 INCH ROUND SHALLOW SPECULAR CLEAR TRIM, WITH 65° OPTIC  
Light Source: (1) HIGH LUMEN LED 90CRI / 3500K CCT  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 4736.4 lumens  
Efficiency: N/A  
Efficacy: 100.8 lumens/watt  
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.96  
Luminous Opening: Circular (Dia: 0.48' x H: 0')  
CIE Type: Direct


Input Watts (W): 47  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT



Downlight

TEST NUMBER: P749679  
CATALOG NUMBER: LD4D50D010-EU4DR6540509035-4LBS1LI

### Luminous Intensity Polar Plot





TEST NUMBER: P749679

CATALOG NUMBER: LD4D50D010-EU4DR6540509035-4LBS1LI

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20			
RC	80				70				50				30				10		0	
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	113	110	107	105	111	108	105	103	104	102	100		100	99	97		97	95	94	93
2	107	102	97	94	105	100	96	92	97	93	90		94	91	88		91	89	87	85
3	101	94	88	84	99	92	87	83	90	86	82		87	84	81		85	82	80	78
4	95	87	81	76	93	86	80	76	84	79	75		82	77	74		80	76	73	72
5	90	81	74	70	88	80	74	69	78	73	69		76	72	68		75	71	68	66
6	85	75	69	64	83	74	68	64	73	67	63		71	67	63		70	66	62	61
7	80	70	64	59	79	69	63	59	68	63	59		67	62	58		66	61	58	56
8	76	66	59	55	75	65	59	55	64	58	54		63	58	54		62	57	54	52
9	72	61	55	51	71	61	55	51	60	54	51		59	54	50		58	54	50	49
10	68	58	52	47	67	57	51	47	57	51	47		56	51	47		55	50	47	46

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	251166
5°	250531
10°	250314
15°	242600
20°	220857
25°	192461
30°	160073
35°	126839
40°	91542
45°	57833
50°	30147
55°	16027
60°	8410
65°	4630
70°	1947
75°	2144
80°	1480
85°	1273

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 45°  
 Luminance: 57833 cd/sqm



TEST NUMBER: P749679

CATALOG NUMBER: LD4D50D010-EU4DR6540509035-4LBS1LI

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	406.7	8.6
10°-20°	1113.7	23.5
20°-30°	1361.3	28.7
30°-40°	1104.5	23.3
40°-50°	550.4	11.6
50°-60°	153.5	3.2
60°-70°	34.9	0.7
70°-80°	9.1	0.2
80°-90°	2.3	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2881.6	60.8
0°-40°	3986.2	84.2
0°-60°	4690.1	99.0
0°-90°	4736.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4736.4	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	4300	
5°	4273	407
15°	4012	1114
25°	2987	1361
35°	1779	1105
45°	700	550
55°	157	154
65°	34	35
75°	10	9
85°	2	2
90°	0	



TEST NUMBER: P749679

CATALOG NUMBER: LD4D50D010-EU4DR6540509035-4LBS1LI

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	4300.5
2.5°	4297.3
5°	4273.3
7.5°	4259.4
10°	4220.8
12.5°	4142.5
15°	4012.3
17.5°	3808.8
20°	3553.5
22.5°	3278.0
25°	2986.6
27.5°	2675.1
30°	2373.6
32.5°	2076.0
35°	1779.0
37.5°	1482.6
40°	1200.7
42.5°	936.6
45°	700.2
47.5°	487.9
50°	331.8
52.5°	228.8
55°	157.4
57.5°	106.2
60°	72.0
62.5°	49.9
65°	33.5
67.5°	17.1
70°	11.4
72.5°	10.7
75°	9.5
77.5°	6.3
80°	4.4
82.5°	3.2
85°	1.9
87.5°	1.3
90°	0.0

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report





Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)