

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P750336

Luminaire Tested: LD4D55D010-EU4DR6055659024-4LBDP1B

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P750336
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-57)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D55D010-EU4DR6055659024-4LBDP1B
Description: 4 INCH ROUND DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 60° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2400K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3702.6 lumens
Efficiency: N/A
Efficacy: 63.6 lumens/watt
Spacing Criteria (0/90/45): 0.91 / 0.91 / 0.83
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct


Input Watts (W): 58.2
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



Downlight

TEST NUMBER: P750336
CATALOG NUMBER: LD4D55D010-EU4DR6055659024-4LBDP1B

Luminous Intensity Polar Plot





TEST NUMBER: P750336

CATALOG NUMBER: LD4D55D010-EU4DR6055659024-4LBDP1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	113	110	108	105	111	108	106	104	104	102	100	100	99	97	97	96	95	93																			
2	107	102	98	95	105	101	97	94	97	94	92	94	92	90	92	90	88	86																			
3	102	96	90	86	100	94	89	86	91	88	84	89	86	83	87	84	82	80																			
4	97	89	84	80	95	88	83	79	86	82	78	84	80	77	82	79	76	75																			
5	92	84	78	74	91	83	78	74	81	77	73	80	76	72	78	75	72	70																			
6	88	79	73	69	87	78	73	69	77	72	68	75	71	68	74	70	67	66																			
7	84	75	69	65	83	74	68	64	73	68	64	72	67	64	71	67	63	62																			
8	80	71	65	61	79	70	65	61	69	64	60	68	64	60	67	63	60	59																			
9	77	67	61	57	75	67	61	57	66	61	57	65	60	57	64	60	57	55																			
10	73	64	58	54	72	63	58	54	62	58	54	62	57	54	61	57	54	53																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	480441
5°	492257
10°	498204
15°	474608
20°	418454
25°	338461
30°	228936
35°	114723
40°	18613
45°	18218
50°	18579
55°	18859
60°	19383
65°	19829
70°	20286
75°	20517
80°	19820
85°	16548

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 75°
 Luminance: 20517 cd/sqm



TEST NUMBER: P750336

CATALOG NUMBER: LD4D55D010-EU4DR6055659024-4LBDP1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	429.0	11.6
10°-20°	1160.6	31.3
20°-30°	1248.7	33.7
30°-40°	542.8	14.7
40°-50°	91.2	2.5
50°-60°	88.7	2.4
60°-70°	75.8	2.0
70°-80°	50.7	1.4
80°-90°	15.2	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2838.2	76.7
0°-40°	3381.0	91.3
0°-60°	3560.8	96.2
0°-90°	3702.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3702.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	4397	
5°	4488	429
15°	4196	1161
25°	2808	1249
35°	860	543
45°	118	91
55°	99	89
65°	77	76
75°	49	51
85°	13	15
90°	0	



TEST NUMBER: P750336

CATALOG NUMBER: LD4D55D010-EU4DR6055659024-4LBDP1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	4397.2
2.5°	4520.8
5°	4488.2
7.5°	4498.5
10°	4490.5
12.5°	4397.8
15°	4195.8
17.5°	3924.5
20°	3598.9
22.5°	3250.4
25°	2807.5
27.5°	2245.5
30°	1814.6
32.5°	1398.6
35°	860.1
37.5°	368.0
40°	130.5
42.5°	120.2
45°	117.9
47.5°	113.9
50°	109.3
52.5°	104.2
55°	99.0
57.5°	93.9
60°	88.7
62.5°	83.0
65°	76.7
67.5°	70.4
70°	63.5
72.5°	56.1
75°	48.6
77.5°	40.1
80°	31.5
82.5°	22.3
85°	13.2
87.5°	4.6
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)