

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P750494

Luminaire Tested: LD4D55D010-EU4DR7055659024-4LBDP1LI

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P750494
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-73)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D55D010-EU4DR7055659024-4LBDP1LI
Description: 4 INCH ROUND DEEP 45° CUTOFF SPECULAR CLEAR TRIM, WITH 70° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2400K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4969.2 lumens
Efficiency: N/A
Efficacy: 85.4 lumens/watt
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.82
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct


Input Watts (W): 58.2
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



Downlight

TEST NUMBER: P750494
CATALOG NUMBER: LD4D55D010-EU4DR7055659024-4LBDP1LI

Luminous Intensity Polar Plot





TEST NUMBER: P750494

CATALOG NUMBER: LD4D55D010-EU4DR7055659024-4LBDP1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	112	109	106	103	110	107	104	102	103	101	99	99	97	96	95	94	93	91																			
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	85	83																			
3	100	92	87	82	98	91	86	81	88	84	80	86	82	79	83	80	78	76																			
4	94	86	80	75	92	85	79	74	82	77	73	80	76	73	78	75	72	70																			
5	89	80	74	69	87	79	73	69	77	72	68	75	71	67	74	70	67	65																			
6	85	75	68	64	83	74	68	64	73	67	63	71	66	63	70	66	62	61																			
7	80	70	64	59	79	70	64	59	68	63	59	67	62	59	66	62	58	57																			
8	77	66	60	56	75	66	60	56	65	59	55	64	59	55	63	58	55	53																			
9	73	63	57	52	72	62	56	52	61	56	52	60	55	52	60	55	52	50																			
10	70	59	53	49	69	59	53	49	58	53	49	57	52	49	57	52	49	48																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	610429
5°	592284
10°	575778
15°	568222
20°	530600
25°	398618
30°	281786
35°	99810
40°	52488
45°	55905
50°	57895
55°	58976
60°	59350
65°	58092
70°	54819
75°	50785
80°	45051
85°	36606

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 57.5°
 Luminance: 59358 cd/sqm



TEST NUMBER: P750494

CATALOG NUMBER: LD4D55D010-EU4DR7055659024-4LBDP1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	509.4	10.3
10°-20°	1397.1	28.1
20°-30°	1538.8	31.0
30°-40°	587.9	11.8
40°-50°	277.6	5.6
50°-60°	276.0	5.6
60°-70°	221.0	4.4
70°-80°	127.0	2.6
80°-90°	34.5	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3445.3	69.3
0°-40°	4033.2	81.2
0°-60°	4586.7	92.3
0°-90°	4969.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4969.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	5587	
5°	5400	509
15°	5023	1397
25°	3306	1539
35°	748	588
45°	362	278
55°	310	276
65°	225	221
75°	120	127
85°	29	35
90°	0	



TEST NUMBER: P750494

CATALOG NUMBER: LD4D55D010-EU4DR7055659024-4LBDP1LI

CANDELA DISTRIBUTION (FULL):

0°	
0°	5586.9
2.5°	5528.5
5°	5400.2
7.5°	5293.2
10°	5189.7
12.5°	5102.1
15°	5023.4
17.5°	4833.2
20°	4563.4
22.5°	3981.4
25°	3306.5
27.5°	2878.3
30°	2233.5
32.5°	1442.7
35°	748.3
37.5°	404.2
40°	368.0
42.5°	365.3
45°	361.8
47.5°	353.8
50°	340.6
52.5°	325.5
55°	309.6
57.5°	291.9
60°	271.6
62.5°	248.6
65°	224.7
67.5°	198.1
70°	171.6
72.5°	145.1
75°	120.3
77.5°	94.6
80°	71.6
82.5°	50.4
85°	29.2
87.5°	11.5
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)