

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P751441

Luminaire Tested: LD4D65D010-EU4DR3055659027-4LBDP1B

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P751441
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-16)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D65D010-EU4DR3055659027-4LBDP1B
Description: 4 INCH ROUND DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 30° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 5078.2 lumens
Efficiency: N/A
Efficacy: 69.8 lumens/watt
Spacing Criteria (0/90/45): 0.52 / 0.52 / 0.49
Luminous Opening: Rectangular (W 0.38' x L: 0.38' x H: 0')
CIE Type: Direct

Input Watts (W): 72.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P751441

CATALOG NUMBER: LD4D65D010-EU4DR3055659027-4LBDP1B

Luminous Intensity Polar Plot





TEST NUMBER: P751441

CATALOG NUMBER: LD4D65D010-EU4DR3055659027-4LBDP1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0													
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100						100													
1	115	113	111	109	112	110	109	107	106	105	104	103	102	101	99	99	98	96						96													
2	111	107	104	101	109	105	102	100	102	100	98	99	97	96	97	95	94	92						92													
3	107	102	98	95	105	101	97	94	98	95	93	96	93	91	94	92	90	89						89													
4	103	98	93	90	102	96	93	90	94	91	89	93	90	88	91	89	87	85						85													
5	100	94	89	86	98	93	89	86	91	88	85	90	86	84	88	86	83	82						82													
6	97	90	85	82	95	89	85	82	88	84	81	87	83	81	85	83	80	79						79													
7	94	87	82	79	92	86	82	79	85	81	78	84	81	78	83	80	78	77						77													
8	91	84	79	76	90	83	79	76	82	78	76	81	78	75	80	77	75	74						74													
9	88	81	76	73	87	80	76	73	80	76	73	79	75	73	78	75	73	72						72													
10	85	78	74	71	85	78	74	71	77	73	71	76	73	71	76	73	70	69						69													

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	1249869	1249869	1249869
5°	1213982	1212568	1214044
10°	1051500	1044085	1051243
15°	686051	682366	678935
20°	341137	353942	340681
25°	171843	193777	168321
30°	68799	74968	59943
35°	31911	30565	25622
40°	13779	15298	12980
45°	9721	12059	9807
50°	3346	8788	3537
55°	1922	3643	2028
60°	1347	1592	1347
65°	869	869	869
70°	537	358	537
75°	0	237	0
80°	0	0	0
85°	0	0	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 22.5°
 Vertical Angle: 45°
 Luminance: 12059 cd/sqm



TEST NUMBER: P751441

CATALOG NUMBER: LD4D65D010-EU4DR3055659027-4LBDP1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1435.9	28.3
10°-20°	2312.5	45.5
20°-30°	999.3	19.7
30°-40°	227.8	4.5
40°-50°	78.2	1.5
50°-60°	19.1	0.4
60°-70°	4.9	0.1
70°-80°	0.5	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	4747.7	93.5
0°-40°	4975.4	98.0
0°-60°	5072.7	99.9
0°-90°	5078.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5078.2	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	16329	16329	16329	16329	16329	
5°	15800	15784	15781	15814	15800	1437
15°	8658	8553	8611	8583	8568	2318
25°	2035	2112	2294	2058	1993	974
35°	342	349	327	325	274	232
45°	90	111	111	111	91	64
55°	14	15	27	16	15	14
65°	5	5	5	5	5	5
75°	0	0	1	0	0	1
85°	0	0	0	0	0	0
90°	0	0	0	0	0	0



TEST NUMBER: P751441

CATALOG NUMBER: LD4D65D010-EU4DR3055659027-4LBDP1B

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	16328.9	16328.9	16328.9	16328.9	16328.9
2.5°	16220.6	16209.4	16215.8	16223.8	16227.0
5°	15799.7	15784.5	15781.3	15814.2	15800.5
7.5°	14950.8	14929.1	14896.2	14970.8	15040.5
10°	13528.6	13504.5	13433.2	13468.4	13525.3
12.5°	11428.9	11351.2	11349.6	11461.8	11446.6
15°	8657.5	8553.3	8611.0	8582.9	8567.7
17.5°	5821.9	5781.8	5858.8	5835.5	5735.3
20°	4188.0	4198.5	4345.2	4271.4	4182.4
22.5°	3056.0	3093.7	3267.7	3077.7	3007.9
25°	2034.7	2111.7	2294.4	2057.9	1993.0
27.5°	1251.4	1286.7	1471.9	1235.4	1200.1
30°	778.4	760.8	848.2	727.9	678.2
32.5°	510.7	488.2	516.3	463.4	423.3
35°	341.5	348.7	327.1	324.7	274.2
37.5°	213.3	245.3	216.5	230.9	176.4
40°	137.9	178.0	153.1	169.2	129.9
42.5°	113.0	137.1	125.9	133.9	115.4
45°	89.8	111.4	111.4	111.4	90.6
47.5°	49.7	74.6	95.4	76.2	52.9
50°	28.1	37.7	73.8	39.3	29.7
52.5°	19.2	21.6	50.5	22.4	20.0
55°	14.4	15.2	27.3	16.0	15.2
57.5°	11.2	12.0	14.4	12.0	11.2
60°	8.8	8.8	10.4	9.6	8.8
62.5°	6.4	6.4	7.2	6.4	6.4
65°	4.8	4.8	4.8	4.8	4.8
67.5°	2.4	3.2	3.2	3.2	3.2
70°	2.4	1.6	1.6	1.6	2.4
72.5°	1.6	0.8	0.8	0.8	0.8
75°	0.0	0.0	0.8	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report





— 0°-180° - - 45°-225° - - - - 90°-270°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)