

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P751987

Luminaire Tested: LD4D65D010-EU4DR6555659027-4LBDP1B

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P751987
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-59)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D65D010-EU4DR6555659027-4LBDP1B
Description: 4 INCH ROUND DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4215.9 lumens
Efficiency: N/A
Efficacy: 57.9 lumens/watt
Spacing Criteria (0/90/45): 0.98 / 0.98 / 0.92
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 72.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P751987

CATALOG NUMBER: LD4D65D010-EU4DR6555659027-4LBDP1B

Luminous Intensity Polar Plot





TEST NUMBER: P751987

CATALOG NUMBER: LD4D65D010-EU4DR6555659027-4LBDP1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10		0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	113	111	108	106	111	108	106	104	104	103	101	101	99	98	97	96	95	93		
2	108	103	99	95	106	101	97	94	98	95	92	95	92	90	92	90	88	87		
3	102	96	91	87	100	94	90	86	92	88	85	89	86	83	87	84	82	80		
4	97	89	84	79	95	88	83	79	86	82	78	84	80	77	82	79	76	75		
5	92	83	78	73	90	83	77	73	81	76	72	79	75	72	77	74	71	69		
6	87	78	72	68	86	77	72	68	76	71	67	74	70	67	73	69	66	65		
7	83	73	67	63	81	73	67	63	71	66	62	70	66	62	69	65	62	60		
8	79	69	63	59	77	68	63	59	67	62	58	66	62	58	65	61	58	57		
9	75	65	59	55	74	65	59	55	64	58	55	63	58	55	62	58	54	53		
10	71	61	56	52	70	61	55	52	60	55	51	59	55	51	59	54	51	50		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	453530
5°	453903
10°	469891
15°	470660
20°	433326
25°	369215
30°	282644
35°	199687
40°	117869
45°	47854
50°	17338
55°	9658
60°	5550
65°	3051
70°	3195
75°	2491
80°	2580
85°	2257

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 47854 cd/sqm



TEST NUMBER: P751987

CATALOG NUMBER: LD4D65D010-EU4DR6555659027-4LBDP1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	399.7	9.5
10°-20°	1152.9	27.3
20°-30°	1383.3	32.8
30°-40°	929.6	22.1
40°-50°	278.3	6.6
50°-60°	49.1	1.2
60°-70°	14.0	0.3
70°-80°	6.8	0.2
80°-90°	2.2	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2936.0	69.6
0°-40°	3865.6	91.7
0°-60°	4193.0	99.5
0°-90°	4215.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4215.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	4151	
5°	4138	400
15°	4161	1153
25°	3063	1383
35°	1497	930
45°	310	278
55°	51	49
65°	12	14
75°	6	7
85°	2	2
90°	0	



TEST NUMBER: P751987

CATALOG NUMBER: LD4D65D010-EU4DR6555659027-4LBDP1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	4150.9
2.5°	4168.6
5°	4138.5
7.5°	4201.0
10°	4235.3
12.5°	4227.0
15°	4160.9
17.5°	3999.3
20°	3726.8
22.5°	3405.9
25°	3062.6
27.5°	2675.1
30°	2240.3
32.5°	1846.3
35°	1497.1
37.5°	1152.0
40°	826.4
42.5°	539.7
45°	309.7
47.5°	164.0
50°	102.0
52.5°	70.8
55°	50.7
57.5°	36.6
60°	25.4
62.5°	16.5
65°	11.8
67.5°	10.6
70°	10.0
72.5°	7.7
75°	5.9
77.5°	5.3
80°	4.1
82.5°	2.9
85°	1.8
87.5°	1.2
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)