

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P752117

Luminaire Tested: LD4D65D010-EU4DR7055659050-4LBDP1B

Issue Date: 2/5/2024

**Test Information**

Test Method: LM-79-2019  
Report Number: P752117  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-73)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 2/5/2024  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: PORTFOLIO  
Catalog Number: LD4D65D010-EU4DR7055659050-4LBDP1B  
Description: 4 INCH ROUND DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 70° OPTIC  
Light Source: (1) HIGH LUMEN LED 90CRI / 5000K CCT  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 4163.4 lumens  
Efficiency: N/A  
Efficacy: 57.2 lumens/watt  
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.82  
Luminous Opening: Circular (Dia: 0.35' x H: 0')  
CIE Type: Direct


Input Watts (W): 72.8  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT



Downlight

TEST NUMBER: P752117  
CATALOG NUMBER: LD4D65D010-EU4DR7055659050-4LBDP1B

### Luminous Intensity Polar Plot





TEST NUMBER: P752117

CATALOG NUMBER: LD4D65D010-EU4DR7055659050-4LBDP1B

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	112	109	106	103	110	107	104	102	103	101	99	99	97	96	95	94	93	91																			
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	85	83																			
3	100	92	87	82	98	91	86	81	88	84	80	86	82	79	83	80	78	76																			
4	94	86	80	75	92	85	79	74	82	77	73	80	76	73	78	75	72	70																			
5	89	80	74	69	87	79	73	69	77	72	68	75	71	67	74	70	67	65																			
6	85	75	68	64	83	74	68	64	73	67	63	71	66	63	70	66	62	61																			
7	80	70	64	59	79	70	64	59	68	63	59	67	62	59	66	62	58	57																			
8	77	66	60	56	75	66	60	56	65	59	55	64	59	55	63	58	55	53																			
9	73	63	57	52	72	62	56	52	61	56	52	60	55	52	60	55	52	50																			
10	70	59	53	49	69	59	53	49	58	53	49	57	52	49	57	52	49	48																			

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	511439
5°	496239
10°	482406
15°	476079
20°	444558
25°	333976
30°	236090
35°	83631
40°	43973
45°	46834
50°	48495
55°	49413
60°	49714
65°	48656
70°	45938
75°	42553
80°	37752
85°	30714

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 57.5°  
 Luminance: 49740 cd/sqm



TEST NUMBER: P752117

CATALOG NUMBER: LD4D65D010-EU4DR7055659050-4LBDP1B

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	426.8	10.3
10°-20°	1170.6	28.1
20°-30°	1289.2	31.0
30°-40°	492.6	11.8
40°-50°	232.6	5.6
50°-60°	231.2	5.6
60°-70°	185.1	4.4
70°-80°	106.4	2.6
80°-90°	28.9	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2886.6	69.3
0°-40°	3379.2	81.2
0°-60°	3843.0	92.3
0°-90°	4163.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4163.4	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	4681	
5°	4524	427
15°	4209	1171
25°	2770	1289
35°	627	493
45°	303	233
55°	259	231
65°	188	185
75°	101	106
85°	24	29
90°	0	



TEST NUMBER: P752117

CATALOG NUMBER: LD4D65D010-EU4DR7055659050-4LBDP1B

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	4680.9
2.5°	4632.0
5°	4524.5
7.5°	4434.8
10°	4348.1
12.5°	4274.8
15°	4208.8
17.5°	4049.5
20°	3823.4
22.5°	3335.8
25°	2770.3
27.5°	2411.6
30°	1871.3
32.5°	1208.8
35°	627.0
37.5°	338.7
40°	308.3
42.5°	306.1
45°	303.1
47.5°	296.4
50°	285.3
52.5°	272.7
55°	259.4
57.5°	244.6
60°	227.5
62.5°	208.3
65°	188.2
67.5°	166.0
70°	143.8
72.5°	121.5
75°	100.8
77.5°	79.3
80°	60.0
82.5°	42.2
85°	24.5
87.5°	9.6
90°	0.0

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report





Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)