

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P753473

Luminaire Tested: LD4D75BD010-EU4DR6070959027-4LBS1B

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P753473
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-60)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D75BD010-EU4DR6070959027-4LBS1B
Description: 4 INCH ROUND SHALLOW SPECULAR BLACK TRIM, WITH 60° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 6883.5 lumens
Efficiency: N/A
Efficacy: 95.1 lumens/watt
Spacing Criteria (0/90/45): 0.98 / 0.98 / 0.92
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 72.4
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P753473

CATALOG NUMBER: LD4D75BD010-EU4DR6070959027-4LBS1B

Luminous Intensity Polar Plot





TEST NUMBER: P753473

CATALOG NUMBER: LD4D75BD010-EU4DR6070959027-4LBS1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20
RC	80					70					50					30					10
RW	70	50	30	10		70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																					
0	119	119	119	119		116	116	116	116		111	111	111		106	106	106		102	102	102
1	114	111	108	106		111	109	106	104		105	103	101		101	99	98		97	96	95
2	108	103	99	96		106	101	98	95		98	95	92		95	93	90		92	90	89
3	102	96	91	87		100	95	90	86		92	88	85		90	86	84		87	85	82
4	97	90	84	80		95	88	83	79		86	82	78		84	81	78		82	79	77
5	92	84	78	74		91	83	77	73		81	76	73		79	75	72		78	74	71
6	87	79	73	68		86	78	72	68		76	71	68		75	70	67		74	70	67
7	83	74	68	63		82	73	67	63		72	67	63		71	66	63		69	65	62
8	79	69	63	59		78	69	63	59		68	63	59		67	62	59		66	61	58
9	75	65	59	55		74	65	59	55		64	59	55		63	58	55		62	58	55
10	72	62	56	52		71	61	56	52		61	55	52		60	55	52		59	55	52

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	752643
5°	750802
10°	775747
15°	776546
20°	714508
25°	607734
30°	463070
35°	327468
40°	192293
45°	77599
50°	25905
55°	12477
60°	5113
65°	750
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 77599 cd/sqm



TEST NUMBER: P753473

CATALOG NUMBER: LD4D75BD010-EU4DR6070959027-4LBS1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	660.4	9.6
10°-20°	1901.9	27.6
20°-30°	2276.3	33.1
30°-40°	1522.5	22.1
40°-50°	451.4	6.6
50°-60°	64.9	0.9
60°-70°	6.2	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	4838.5	70.3
0°-40°	6361.0	92.4
0°-60°	6877.3	99.9
0°-90°	6883.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6883.5	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	6888	
5°	6846	660
15°	6865	1902
25°	5041	2276
35°	2455	1522
45°	502	451
55°	66	65
65°	3	6
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P753473

CATALOG NUMBER: LD4D75BD010-EU4DR6070959027-4LBS1B

CANDELA DISTRIBUTION (FULL):

0°	
0°	6888.5
2.5°	6879.7
5°	6845.5
7.5°	6938.3
10°	6992.1
12.5°	6982.3
15°	6865.1
17.5°	6588.6
20°	6145.1
22.5°	5612.6
25°	5041.1
27.5°	4397.3
30°	3670.4
32.5°	3021.7
35°	2455.1
37.5°	1887.5
40°	1348.2
42.5°	889.0
45°	502.2
47.5°	256.9
50°	152.4
52.5°	98.7
55°	65.5
57.5°	42.0
60°	23.4
62.5°	9.8
65°	2.9
67.5°	1.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)