

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P753587

Luminaire Tested: LD4D75BD010-EU4DR6570959040-4LBDP1H

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P753587
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-59)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D75BD010-EU4DR6570959040-4LBDP1H
Description: 4 INCH ROUND DEEP 45° CUTOFF SEMI-SPECULAR CLEAR TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 4000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 6644.9 lumens
Efficiency: N/A
Efficacy: 91.8 lumens/watt
Spacing Criteria (0/90/45): 0.98 / 0.98 / 0.92
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 72.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P753587

CATALOG NUMBER: LD4D75BD010-EU4DR6570959040-4LBDP1H

Luminous Intensity Polar Plot





TEST NUMBER: P753587

CATALOG NUMBER: LD4D75BD010-EU4DR6570959040-4LBDP1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20
RC	80					70					50					30					10
RW	70	50	30	10		70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																					
0	119	119	119	119		116	116	116	116		111	111	111		106	106	106		102	102	102
1	113	111	108	106		111	108	106	104		104	103	101		101	99	98		97	96	95
2	108	103	99	95		106	101	97	94		98	95	92		95	92	90		92	90	88
3	102	96	91	87		100	94	90	86		92	88	85		89	86	83		87	84	82
4	97	89	84	79		95	88	83	79		86	82	78		84	80	77		82	79	76
5	92	83	78	73		90	83	77	73		81	76	72		79	75	72		77	74	71
6	87	78	72	68		86	77	72	68		76	71	67		74	70	67		73	69	66
7	83	73	67	63		81	73	67	63		71	66	62		70	66	62		69	65	62
8	79	69	63	59		77	68	63	59		67	62	58		66	62	58		65	61	58
9	75	65	59	55		74	65	59	55		64	58	55		63	58	55		62	58	54
10	71	61	56	52		70	61	55	52		60	55	51		59	55	51		59	54	51

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	714817
5°	715408
10°	740600
15°	741820
20°	682975
25°	581923
30°	445483
35°	314730
40°	185775
45°	75420
50°	27333
55°	15239
60°	8741
65°	4809
70°	5047
75°	3926
80°	4090
85°	3510

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 75420 cd/sqm



TEST NUMBER: P753587

CATALOG NUMBER: LD4D75BD010-EU4DR6570959040-4LBDP1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	630.0	9.5
10°-20°	1817.2	27.3
20°-30°	2180.3	32.8
30°-40°	1465.2	22.1
40°-50°	438.6	6.6
50°-60°	77.4	1.2
60°-70°	22.0	0.3
70°-80°	10.8	0.2
80°-90°	3.4	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	4627.4	69.6
0°-40°	6092.6	91.7
0°-60°	6608.7	99.5
0°-90°	6644.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6644.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	6542	
5°	6523	630
15°	6558	1817
25°	4827	2180
35°	2360	1465
45°	488	439
55°	80	77
65°	19	22
75°	9	11
85°	3	3
90°	0	



TEST NUMBER: P753587

CATALOG NUMBER: LD4D75BD010-EU4DR6570959040-4LBDP1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	6542.3
2.5°	6570.2
5°	6522.8
7.5°	6621.4
10°	6675.3
12.5°	6662.3
15°	6558.1
17.5°	6303.4
20°	5873.9
22.5°	5368.1
25°	4827.0
27.5°	4216.2
30°	3531.0
32.5°	2910.0
35°	2359.6
37.5°	1815.7
40°	1302.5
42.5°	850.7
45°	488.1
47.5°	258.5
50°	160.8
52.5°	111.6
55°	80.0
57.5°	57.6
60°	40.0
62.5°	26.0
65°	18.6
67.5°	16.7
70°	15.8
72.5°	12.1
75°	9.3
77.5°	8.4
80°	6.5
82.5°	4.6
85°	2.8
87.5°	1.9
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)