

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P754331

Luminaire Tested: LD4D80BD010-EU4DR6570959027-4LBS1B

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P754331
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-147)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D80BD010-EU4DR6570959027-4LBS1B
Description: 4 INCH ROUND SHALLOW SPECULAR BLACK TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 6326.3 lumens
Efficiency: N/A
Efficacy: 80.2 lumens/watt
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.96
Luminous Opening: Circular (Dia: 0.48' x H: 0')
CIE Type: Direct

Input Watts (W): 78.9
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P754331

CATALOG NUMBER: LD4D80BD010-EU4DR6570959027-4LBS1B

Luminous Intensity Polar Plot





TEST NUMBER: P754331

CATALOG NUMBER: LD4D80BD010-EU4DR6570959027-4LBS1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	113	110	107	105	111	108	105	103	104	102	100	100	99	97	97	95	94	93																			
2	107	102	97	94	105	100	96	92	97	93	90	94	91	88	91	89	87	85																			
3	101	94	88	84	99	92	87	83	90	86	82	87	84	81	85	82	80	78																			
4	95	87	81	76	93	86	80	76	84	79	75	82	77	74	80	76	73	72																			
5	90	81	74	70	88	80	74	69	78	73	69	76	72	68	75	71	68	66																			
6	85	75	69	64	83	74	68	64	73	67	63	71	67	63	70	66	62	61																			
7	80	70	64	59	79	69	63	59	68	63	59	67	62	58	66	61	58	56																			
8	76	66	59	55	75	65	59	55	64	58	54	63	58	54	62	57	54	52																			
9	72	61	55	51	71	61	55	51	60	54	51	59	54	50	58	54	50	49																			
10	68	58	52	47	67	57	51	47	57	51	47	56	51	47	55	50	47	46																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	335478
5°	334631
10°	334349
15°	324039
20°	294999
25°	257070
30°	213815
35°	169411
40°	122275
45°	77252
50°	40269
55°	21403
60°	11237
65°	6177
70°	2596
75°	2866
80°	1984
85°	1675

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 77252 cd/sqm



TEST NUMBER: P754331

CATALOG NUMBER: LD4D80BD010-EU4DR6570959027-4LBS1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	543.2	8.6
10°-20°	1487.5	23.5
20°-30°	1818.3	28.7
30°-40°	1475.3	23.3
40°-50°	735.2	11.6
50°-60°	205.1	3.2
60°-70°	46.6	0.7
70°-80°	12.1	0.2
80°-90°	3.1	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3849.0	60.8
0°-40°	5324.3	84.2
0°-60°	6264.5	99.0
0°-90°	6326.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6326.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	5744	
5°	5708	543
15°	5359	1488
25°	3989	1818
35°	2376	1475
45°	935	735
55°	210	205
65°	45	47
75°	13	12
85°	2	3
90°	0	



TEST NUMBER: P754331

CATALOG NUMBER: LD4D80BD010-EU4DR6570959027-4LBS1B

CANDELA DISTRIBUTION (FULL):

0°	
0°	5744.1
2.5°	5739.9
5°	5707.8
7.5°	5689.3
10°	5637.8
12.5°	5533.1
15°	5359.2
17.5°	5087.4
20°	4746.4
22.5°	4378.4
25°	3989.2
27.5°	3573.1
30°	3170.5
32.5°	2772.9
35°	2376.1
37.5°	1980.3
40°	1603.8
42.5°	1251.0
45°	935.3
47.5°	651.6
50°	443.2
52.5°	305.6
55°	210.2
57.5°	141.8
60°	96.2
62.5°	66.7
65°	44.7
67.5°	22.8
70°	15.2
72.5°	14.3
75°	12.7
77.5°	8.4
80°	5.9
82.5°	4.2
85°	2.5
87.5°	1.7
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)