

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P755114

Luminaire Tested: LD4D85BD010-EU4DR6570959027-4LBS1MW

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P755114
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-147)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D85BD010-EU4DR6570959027-4LBS1MW
Description: 4 INCH ROUND SHALLOW MATTE WHITE TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 6892.7 lumens
Efficiency: N/A
Efficacy: 78.6 lumens/watt
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.96
Luminous Opening: Circular (Dia: 0.48' x H: 0')
CIE Type: Direct

Input Watts (W): 87.7
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P755114

CATALOG NUMBER: LD4D85BD010-EU4DR6570959027-4LBS1MW

Luminous Intensity Polar Plot





TEST NUMBER: P755114

CATALOG NUMBER: LD4D85BD010-EU4DR6570959027-4LBS1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10		0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	113	110	107	105	111	108	105	103	104	102	100	100	99	97	97	95	94	93		
2	107	102	97	94	105	100	96	92	97	93	90	94	91	88	91	89	87	85		
3	101	94	88	84	99	92	87	83	90	86	82	87	84	81	85	82	80	78		
4	95	87	81	76	93	86	80	76	84	79	75	82	77	74	80	76	73	72		
5	90	81	74	70	88	80	74	69	78	73	69	76	72	68	75	71	68	66		
6	85	75	69	64	83	74	68	64	73	67	63	71	67	63	70	66	62	61		
7	80	70	64	59	79	69	63	59	68	63	59	67	62	58	66	61	58	56		
8	76	66	59	55	75	65	59	55	64	58	54	63	58	54	62	57	54	52		
9	72	61	55	51	71	61	55	51	60	54	51	59	54	50	58	54	50	49		
10	68	58	52	47	67	57	51	47	57	51	47	56	51	47	55	50	47	46		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	365515
5°	364589
10°	364280
15°	353050
20°	321407
25°	280089
30°	232954
35°	184583
40°	133223
45°	84165
50°	43867
55°	23318
60°	12241
65°	6730
70°	2835
75°	3114
80°	2153
85°	1876

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 84165 cd/sqm



TEST NUMBER: P755114

CATALOG NUMBER: LD4D85BD010-EU4DR6570959027-4LBS1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	591.8	8.6
10°-20°	1620.7	23.5
20°-30°	1981.0	28.7
30°-40°	1607.4	23.3
40°-50°	801.0	11.6
50°-60°	223.4	3.2
60°-70°	50.8	0.7
70°-80°	13.2	0.2
80°-90°	3.4	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	4193.6	60.8
0°-40°	5800.9	84.2
0°-60°	6825.3	99.0
0°-90°	6892.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6892.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	6258	
5°	6219	592
15°	5839	1621
25°	4346	1981
35°	2589	1607
45°	1019	801
55°	229	223
65°	49	51
75°	14	13
85°	3	3
90°	0	



TEST NUMBER: P755114

CATALOG NUMBER: LD4D85BD010-EU4DR6570959027-4LBS1MW

CANDELA DISTRIBUTION (FULL):

	0°
0°	6258.4
2.5°	6253.8
5°	6218.8
7.5°	6198.6
10°	6142.5
12.5°	6028.4
15°	5839.0
17.5°	5542.9
20°	5171.3
22.5°	4770.3
25°	4346.4
27.5°	3893.0
30°	3454.3
32.5°	3021.1
35°	2588.9
37.5°	2157.5
40°	1747.4
42.5°	1363.0
45°	1019.0
47.5°	710.0
50°	482.8
52.5°	332.9
55°	229.0
57.5°	154.5
60°	104.8
62.5°	72.7
65°	48.7
67.5°	24.8
70°	16.6
72.5°	15.6
75°	13.8
77.5°	9.2
80°	6.4
82.5°	4.6
85°	2.8
87.5°	1.8
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)