

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P755978

Luminaire Tested: LD4D90BD010-EU4DR7070959030-4LBDP1B

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P755978
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-73)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D90BD010-EU4DR7070959030-4LBDP1B
Description: 4 INCH ROUND DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 70° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 5047.9 lumens
Efficiency: N/A
Efficacy: 51.0 lumens/watt
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.82
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct


Input Watts (W): 98.9
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



Downlight

TEST NUMBER: P755978
CATALOG NUMBER: LD4D90BD010-EU4DR7070959030-4LBDP1B

Luminous Intensity Polar Plot





TEST NUMBER: P755978
 CATALOG NUMBER: LD4D90BD010-EU4DR7070959030-4LBDP1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	112	109	106	103	110	107	104	102	103	101	99	99	97	96	95	94	93	91																			
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	85	83																			
3	100	92	87	82	98	91	86	81	88	84	80	86	82	79	83	80	78	76																			
4	94	86	80	75	92	85	79	74	82	77	73	80	76	73	78	75	72	70																			
5	89	80	74	69	87	79	73	69	77	72	68	75	71	67	74	70	67	65																			
6	85	75	68	64	83	74	68	64	73	67	63	71	66	63	70	66	62	61																			
7	80	70	64	59	79	70	64	59	68	63	59	67	62	59	66	62	58	57																			
8	77	66	60	56	75	66	60	56	65	59	55	64	59	55	63	58	55	53																			
9	73	63	57	52	72	62	56	52	61	56	52	60	55	52	60	55	52	50																			
10	70	59	53	49	69	59	53	49	58	53	49	57	52	49	57	52	49	48																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	620077
5°	601650
10°	584887
15°	577215
20°	538994
25°	404923
30°	286240
35°	101398
40°	53315
45°	56785
50°	58796
55°	59909
60°	60290
65°	58997
70°	55681
75°	51587
80°	45806
85°	37233

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 57.5°
 Luminance: 60294 cd/sqm



TEST NUMBER: P755978

CATALOG NUMBER: LD4D90BD010-EU4DR7070959030-4LBDP1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	517.4	10.3
10°-20°	1419.2	28.1
20°-30°	1563.1	31.0
30°-40°	597.2	11.8
40°-50°	282.0	5.6
50°-60°	280.4	5.6
60°-70°	224.5	4.4
70°-80°	129.0	2.6
80°-90°	35.1	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3499.8	69.3
0°-40°	4097.0	81.2
0°-60°	4659.3	92.3
0°-90°	5047.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5047.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	5675	
5°	5486	517
15°	5103	1419
25°	3359	1563
35°	760	597
45°	368	282
55°	314	280
65°	228	224
75°	122	129
85°	30	35
90°	0	



TEST NUMBER: P755978

CATALOG NUMBER: LD4D90BD010-EU4DR7070959030-4LBDP1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	5675.2
2.5°	5615.9
5°	5485.6
7.5°	5376.9
10°	5271.8
12.5°	5182.8
15°	5102.9
17.5°	4909.7
20°	4635.6
22.5°	4044.4
25°	3358.8
27.5°	2923.9
30°	2268.8
32.5°	1465.5
35°	760.2
37.5°	410.6
40°	373.8
42.5°	371.1
45°	367.5
47.5°	359.4
50°	345.9
52.5°	330.7
55°	314.5
57.5°	296.5
60°	275.9
62.5°	252.5
65°	228.2
67.5°	201.3
70°	174.3
72.5°	147.4
75°	122.2
77.5°	96.1
80°	72.8
82.5°	51.2
85°	29.7
87.5°	11.7
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)