

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P755536

Luminaire Tested: LD4D90BD010-EU4DR4070959040-4LBDP1B

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P755536
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-28)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D90BD010-EU4DR4070959040-4LBDP1B
Description: 4 INCH ROUND DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 40° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 4000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 8458.5 lumens
Efficiency: N/A
Efficacy: 85.5 lumens/watt
Spacing Criteria (0/90/45): 0.68 / 0.68 / 0.6
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct


Input Watts (W): 98.9
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



Downlight

TEST NUMBER: P755536
CATALOG NUMBER: LD4D90BD010-EU4DR4070959040-4LBDP1B

Luminous Intensity Polar Plot





TEST NUMBER: P755536

CATALOG NUMBER: LD4D90BD010-EU4DR4070959040-4LBDP1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10		0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	
1	115	112	110	108	112	110	108	107	106	105	103	103	101	100	99	98	97	96	96	
2	110	106	103	100	108	105	102	99	102	99	97	99	97	95	96	95	93	92	92	
3	106	101	97	94	104	100	96	93	97	94	92	95	93	90	93	91	89	88	88	
4	102	97	92	89	101	95	91	88	93	90	87	92	89	86	90	87	85	84	84	
5	99	92	88	84	97	91	87	84	90	86	83	88	85	83	87	84	82	81	81	
6	95	88	84	80	94	88	83	80	86	82	80	85	82	79	84	81	79	77	77	
7	92	85	80	77	91	84	80	77	83	79	76	82	79	76	81	78	76	74	74	
8	89	82	77	74	88	81	77	74	80	76	73	79	76	73	78	75	73	72	72	
9	86	79	74	71	85	78	74	71	77	73	71	76	73	70	76	72	70	69	69	
10	83	76	71	68	82	75	71	68	75	71	68	74	70	68	73	70	68	67	67	

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	2151727
5°	2141268
10°	2023971
15°	1720627
20°	1172728
25°	489312
30°	153856
35°	71506
40°	39551
45°	18125
50°	8805
55°	4819
60°	2513
65°	905
70°	383
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 18125 cd/sqm



TEST NUMBER: P755536

CATALOG NUMBER: LD4D90BD010-EU4DR4070959040-4LBDP1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1823.0	21.6
10°-20°	4084.0	48.3
20°-30°	2044.3	24.2
30°-40°	374.8	4.4
40°-50°	103.4	1.2
50°-60°	24.3	0.3
60°-70°	4.7	0.1
70°-80°	0.2	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	7951.2	94.0
0°-40°	8326.0	98.4
0°-60°	8453.7	99.9
0°-90°	8458.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	8458.5	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	19694	
5°	19523	###
15°	15211	4084
25°	4059	2044
35°	536	375
45°	117	103
55°	25	24
65°	4	5
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P755536

CATALOG NUMBER: LD4D90BD010-EU4DR4070959040-4LBDP1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	19693.5
2.5°	19664.7
5°	19523.2
7.5°	19072.2
10°	18242.8
12.5°	16949.7
15°	15211.3
17.5°	12950.7
20°	10086.0
22.5°	6876.3
25°	4058.8
27.5°	2145.6
30°	1219.5
32.5°	788.1
35°	536.1
37.5°	383.1
40°	277.3
42.5°	189.8
45°	117.3
47.5°	74.8
50°	51.8
52.5°	36.8
55°	25.3
57.5°	16.1
60°	11.5
62.5°	6.9
65°	3.5
67.5°	2.3
70°	1.2
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)