

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P743283

Luminaire Tested: LD4D15D010-EU4DR400215IC9030-4LBCSSQMW

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P743283
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-28)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D15D010-EU4DR400215IC9030-4LBCSSQMW
Description: 4 INCH SQAURE SHALLOW CAST MATTE WHITE TRIM, WITH 40° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1327.1 lumens
Efficiency: N/A
Efficacy: 84.0 lumens/watt
Spacing Criteria (0/90/45): 0.68 / 0.68 / 0.6
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 15.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P743283
CATALOG NUMBER: LD4D15D010-EU4DR400215IC9030-4LBCSSQMW

Luminous Intensity Polar Plot





TEST NUMBER: P743283

CATALOG NUMBER: LD4D15D010-EU4DR400215IC9030-4LBCSSQMW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									20									20
RC	80									70									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																														
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																												
1	115	112	110	108	112	110	108	107	106	105	103	103	101	100	99	98	97	96																												
2	110	106	103	100	108	105	102	99	102	99	97	99	97	95	96	95	93	92																												
3	106	101	97	94	104	100	96	93	97	94	92	95	93	90	93	91	89	88																												
4	102	97	92	89	101	95	91	88	93	90	87	92	89	86	90	87	85	84																												
5	99	92	88	84	97	91	87	84	90	86	83	88	85	83	87	84	82	81																												
6	95	88	84	80	94	88	83	80	86	82	80	85	82	79	84	81	79	77																												
7	92	85	80	77	91	84	80	77	83	79	76	82	79	76	81	78	76	74																												
8	89	82	77	74	88	81	77	74	80	76	73	79	76	73	78	75	73	72																												
9	86	79	74	71	85	78	74	71	77	73	71	77	73	70	76	72	70	69																												
10	83	76	71	68	82	75	71	68	75	71	68	74	70	68	73	70	68	67																												

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	337616
5°	335977
10°	317573
15°	269972
20°	184002
25°	76770
30°	24148
35°	11217
40°	6204
45°	2843
50°	1377
55°	762
60°	393
65°	129
70°	64
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 2843 cd/sqm



TEST NUMBER: P743283

CATALOG NUMBER: LD4D15D010-EU4DR400215IC9030-4LBCSSQMW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	286.0	21.6
10°-20°	640.8	48.3
20°-30°	320.8	24.2
30°-40°	58.8	4.4
40°-50°	16.2	1.2
50°-60°	3.8	0.3
60°-70°	0.7	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1247.6	94.0
0°-40°	1306.4	98.4
0°-60°	1326.4	99.9
0°-90°	1327.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1327.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3090	
5°	3063	286
15°	2387	641
25°	637	321
35°	84	59
45°	18	16
55°	4	4
65°	0	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P743283

CATALOG NUMBER: LD4D15D010-EU4DR400215IC9030-4LBCSSQMW

CANDELA DISTRIBUTION (FULL):

	0°
0°	3090.0
2.5°	3085.5
5°	3063.3
7.5°	2992.6
10°	2862.4
12.5°	2659.5
15°	2386.7
17.5°	2032.0
20°	1582.5
22.5°	1078.9
25°	636.8
27.5°	336.7
30°	191.4
32.5°	123.6
35°	84.1
37.5°	60.1
40°	43.5
42.5°	29.8
45°	18.4
47.5°	11.7
50°	8.1
52.5°	5.8
55°	4.0
57.5°	2.5
60°	1.8
62.5°	1.1
65°	0.5
67.5°	0.3
70°	0.2
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)