

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P739222

Luminaire Tested: LD4D02D010-EU4DR400210IC9024-4LBSQW1B

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P739222
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-28)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D02D010-EU4DR400210IC9024-4LBSQW1B
Description: 4 INCH SQAURE DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 40° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2400K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 271.2 lumens
Efficiency: N/A
Efficacy: 53.2 lumens/watt
Spacing Criteria (0/90/45): 0.68 / 0.68 / 0.6
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 5.1
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P739222
CATALOG NUMBER: LD4D02D010-EU4DR400210IC9024-4LBSQW1B

Luminous Intensity Polar Plot





TEST NUMBER: P739222

CATALOG NUMBER: LD4D02D010-EU4DR400210IC9024-4LBSQW1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									20									
RC	80									70									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																			
RCR																																														
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																												
1	115	112	110	108	112	110	108	107	106	105	103	103	101	100	99	98	97	96																												
2	110	106	103	100	108	105	102	99	102	99	97	99	97	95	96	95	93	92																												
3	106	101	97	94	104	100	96	93	97	94	92	95	93	90	93	91	89	88																												
4	102	97	92	89	101	95	91	88	93	90	87	92	89	86	90	87	85	84																												
5	99	92	88	84	97	91	87	84	90	86	83	88	85	83	87	84	82	81																												
6	95	88	84	80	94	88	83	80	86	82	80	85	82	79	84	81	79	77																												
7	92	85	80	77	91	84	80	77	83	79	76	82	79	76	81	78	76	74																												
8	89	82	77	74	88	81	77	74	80	76	73	79	76	73	78	75	73	72																												
9	86	79	74	71	85	78	74	71	77	73	71	76	73	70	76	72	70	69																												
10	83	76	71	68	82	75	71	68	75	71	68	74	70	68	73	70	68	67																												

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	68987
5°	68648
10°	64892
15°	55166
20°	37603
25°	15684
30°	4933
35°	2294
40°	1269
45°	587
50°	289
55°	152
60°	66
65°	26
70°	32
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 587 cd/sqm



TEST NUMBER: P739222

CATALOG NUMBER: LD4D02D010-EU4DR400210IC9024-4LBSQW1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	58.4	21.5
10°-20°	130.9	48.3
20°-30°	65.5	24.2
30°-40°	12.0	4.4
40°-50°	3.3	1.2
50°-60°	0.8	0.3
60°-70°	0.1	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	254.9	94.0
0°-40°	267.0	98.4
0°-60°	271.1	99.9
0°-90°	271.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	271.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	631	
5°	626	58
15°	488	131
25°	130	66
35°	17	12
45°	4	3
55°	1	1
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P739222

CATALOG NUMBER: LD4D02D010-EU4DR400210IC9024-4LBSQW1B

CANDELA DISTRIBUTION (FULL):

0°	
0°	631.4
2.5°	630.5
5°	625.9
7.5°	611.5
10°	584.9
12.5°	543.4
15°	487.7
17.5°	415.2
20°	323.4
22.5°	220.5
25°	130.1
27.5°	68.8
30°	39.1
32.5°	25.3
35°	17.2
37.5°	12.3
40°	8.9
42.5°	6.1
45°	3.8
47.5°	2.4
50°	1.7
52.5°	1.2
55°	0.8
57.5°	0.5
60°	0.3
62.5°	0.2
65°	0.1
67.5°	0.1
70°	0.1
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)