

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P744897

Luminaire Tested: LD4D25D010-EU4DR2015309027-4LBSQW1B

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P744897
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2310-195-36)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D25D010-EU4DR2015309027-4LBSQW1B
Description: 4 INCH SQAURE DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 20° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1954.6 lumens
Efficiency: N/A
Efficacy: 77.9 lumens/watt
Spacing Criteria (0/90/45): 0.34 / 0.34 / 0.36
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 25.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P744897

CATALOG NUMBER: LD4D25D010-EU4DR2015309027-4LBSQW1B

Luminous Intensity Polar Plot





TEST NUMBER: P744897

CATALOG NUMBER: LD4D25D010-EU4DR2015309027-4LBSQW1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	115	113	111	109	113	111	109	108	107	106	104	103	102	101	100	99	98	97
2	111	108	105	102	109	106	104	101	103	101	99	100	99	97	98	96	95	94
3	108	103	100	97	106	102	99	96	100	97	95	97	95	93	95	93	92	91
4	105	99	96	93	103	98	95	92	96	93	91	95	92	90	93	91	89	88
5	102	96	92	89	100	95	91	89	94	90	88	92	89	87	91	88	86	85
6	99	93	89	86	98	92	88	86	91	87	85	90	87	84	88	86	84	83
7	96	90	86	83	95	89	86	83	88	85	82	87	84	82	86	84	82	81
8	94	87	83	81	93	87	83	80	86	83	80	85	82	80	84	82	80	79
9	91	85	81	78	91	85	81	78	84	80	78	83	80	78	82	80	78	77
10	89	83	79	76	88	82	79	76	82	78	76	81	78	76	81	78	76	75

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1215537
5°	1096639
10°	615497
15°	312865
20°	132470
25°	61146
30°	32374
35°	17446
40°	9328
45°	5516
50°	3196
55°	1695
60°	1093
65°	776
70°	319
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 5516 cd/sqm



TEST NUMBER: P744897

CATALOG NUMBER: LD4D25D010-EU4DR2015309027-4LBSQW1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	792.1	40.5
10°-20°	780.0	39.9
20°-30°	254.8	13.0
30°-40°	86.8	4.4
40°-50°	29.2	1.5
50°-60°	8.8	0.4
60°-70°	3.0	0.2
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1826.8	93.5
0°-40°	1913.6	97.9
0°-60°	1951.5	99.8
0°-90°	1954.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1954.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	11125	
5°	9999	792
15°	2766	780
25°	507	255
35°	131	87
45°	36	29
55°	9	9
65°	3	3
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P744897

CATALOG NUMBER: LD4D25D010-EU4DR2015309027-4LBSQW1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	11125.1
0.5°	11125.1
1°	11111.2
1.5°	11083.5
2°	11032.9
2.5°	10965.6
3°	10870.5
3.5°	10737.7
4°	10540.6
4.5°	10300.9
5°	9998.7
5.5°	9601.4
6°	9194.3
6.5°	8727.7
7°	8271.0
7.5°	7736.0
8°	7258.5
8.5°	6778.1
9°	6334.3
9.5°	5927.1
10°	5547.7
12.5°	3983.4
15°	2765.9
17.5°	1807.0
20°	1139.3
22.5°	738.0
25°	507.2
27.5°	356.6
30°	256.6
32.5°	184.3
35°	130.8
37.5°	91.1
40°	65.4
42.5°	47.6
45°	35.7
47.5°	27.7
50°	18.8
52.5°	11.9
55°	8.9
57.5°	6.9
60°	5.0
62.5°	4.0
65°	3.0



TEST NUMBER: P744897

CATALOG NUMBER: LD4D25D010-EU4DR2015309027-4LBSQW1B

CANDELA DISTRIBUTION (continued):

	0°
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



67.5°		2.0
70°		1.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)