Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled data based on original data using

LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P745368

Luminaire Tested: LD4D25D010-EU4DR5020359030-4LBCSSQMMS

Issue Date: 1/30/2024

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report

Test Information

Test Method:	LM-79-2019
Report Number:	P745368
	TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-44)
Test Lab:	COOPER LIGHTING SOLUTIONS
Issue Date:	1/30/2024
Manufacturer:	COOPER LIGHTING SOLUTIONS
Product Line:	PORTFOLIO
Catalog Number:	LD4D25D010-EU4DR5020359030-4LBCSSQMMS
Description:	4 INCH SQAURE SHALLOW CAST MATTE METALLIC SILVER TRIM, WITH 50° OPTIC
Light Source:	(1) HIGH LUMEN LED 90CRI / 3000K CCT
Ballast/Driver:	-

Summary

Lumens per Lamp:	N/A
Luminaire Lumens:	2386.8 lumens
Efficiency:	N/A
Efficacy:	95.1 lumens/watt
Spacing Criteria (0/90/45):	0.8 / 0.8 / 0.73
Luminous Opening:	Circular (Dia: 0.35' x H: 0')
CIE Type:	Direct

Input Watts (W):	25.1
Input Voltage (V):	NR
Input Current (Ain):	NR
Voltage Rise (V):	NR
Power Factor:	NR
Total Harmonic Distortion (THDi):	NR
Frequency (hertz):	60
Stabilization Time:	NR
Operation Time:	NR
Ambient Temperature (°C):	NR
Test Distance:	24 FT

Downlight

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report

TEST NUMBER: P745368
CATALOG NUMBER: LD4D25D010-EU4DR5020359030-4LBCSSQMMS

Luminous Intensity Polar Plot



Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report

TEST NUMBER: P745368
CATALOG NUMBER: LD4D25D010-EU4DR5020359030-4LBCSSQMMS

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20			20			20			20
RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	114	112	109	107	112	110	108	106	106	104	102	102	101	99	98	97	97	95
2	109	105	101	98	107	103	100	97	100	98	95	97	95	93	95	93	91	90
3	105	99	95	91	103	98	94	90	95	92	89	93	90	88	91	88	86	85
4	100	94	89	85	99	93	88	85	90	87	84	89	85	83	87	84	82	80
5	96	89	84	80	95	88	83	79	86	82	79	85	81	78	83	80	77	76
6	92	84	79	75	91	83	79	75	82	78	74	81	77	74	79	76	74	72
7	88	80	75	71	87	79	74	71	78	74	71	77	73	70	76	73	70	69
8	85	76	71	67	84	76	71	67	75	70	67	74	70	67	73	69	66	65
9	81	73	68	64	80	72	67	64	71	67	64	71	67	64	70	66	63	62
10	78	70	64	61	77	69	64	61	68	64	61	68	64	61	67	63	60	59

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	420184
5°	415779
10°	408926
15°	372363
20°	309856
25°	219942
30°	116411
35°	47444
40°	17615
45°	8066
50°	3315
55°	1733
60°	852
65°	259
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 45°
Luminance: 8066 cd/sqm

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report

TEST NUMBER: P745368
CATALOG NUMBER: LD4D25D010-EU4DR5020359030-4LBCSSQMMS

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	358.3	15.0
10°-20°	905.5	37.9
20°-30°	813.4	34.1
30°-40°	254.7	10.7
40°-50°	44.6	1.9
50°-60°	8.9	0.4
60°-70°	1.4	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2077.3	87.0
0°-40°	2331.9	97.7
0°-60°	2385.4	99.9
0°-90°	2386.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2386.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3846	
5°	3791	358
15°	3292	906
25°	1824	813
35°	356	255
45°	52	45
55°	9	9
65°	1	1
75°	0	0
85°	0	0
90°	0	

TEST NUMBER: P745368
CATALOG NUMBER: LD4D25D010-EU4DR5020359030-4LBCSSQMMS

CANDELA DISTRIBUTION (FULL):

	0°
0°	3845.7
2.5°	3826.6
5°	3790.9
7.5°	3736.4
10°	3685.8
12.5°	3523.7
15°	3291.9
17.5°	2997.5
20°	2664.9
22.5°	2280.0
25°	1824.4
27.5°	1341.3
30°	922.7
32.5°	600.8
35°	355.7
37.5°	204.3
40°	123.5
42.5°	80.4
45°	52.2
47.5°	31.8
50°	19.5
52.5°	13.3
55°	9.1
57.5°	6.2
60°	3.9
62.5°	2.3
65°	1.0
67.5°	0.3
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Report Generated By 670245859 / DESKTOP-T8S5UU9

0°-180°

(END OF REPORT)