

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P748173

Luminaire Tested: LD4D40BD010-EU4DR7040509027-4LBSQW1B

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P748173
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-73)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D40BD010-EU4DR7040509027-4LBSQW1B
Description: 4 INCH SQAURE DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 70° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2276.8 lumens
Efficiency: N/A
Efficacy: 64.7 lumens/watt
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.82
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 35.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P748173
CATALOG NUMBER: LD4D40BD010-EU4DR7040509027-4LBSQW1B

Luminous Intensity Polar Plot





TEST NUMBER: P748173

CATALOG NUMBER: LD4D40BD010-EU4DR7040509027-4LBSQW1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	112	109	106	103	110	107	104	102	103	101	99	99	97	96	95	94	93	91																			
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	85	83																			
3	100	92	87	82	98	91	86	81	88	84	80	86	82	79	83	80	78	76																			
4	94	86	80	75	92	85	79	74	82	77	73	80	76	73	78	75	72	70																			
5	89	80	74	69	87	79	73	69	77	72	68	75	71	67	74	70	67	65																			
6	85	75	68	64	83	74	68	64	73	67	63	71	66	63	70	66	62	61																			
7	80	70	64	59	79	70	64	59	68	63	59	67	62	59	66	62	58	57																			
8	77	66	60	56	75	66	60	56	65	59	55	64	59	55	63	58	55	53																			
9	73	63	57	52	72	62	56	52	61	56	52	60	55	52	60	55	52	50																			
10	70	59	53	49	69	59	53	49	58	53	49	57	52	49	57	52	49	48																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	279686
5°	271377
10°	263808
15°	260346
20°	243115
25°	182642
30°	129103
35°	45737
40°	24047
45°	25619
50°	26517
55°	27031
60°	27184
65°	26603
70°	25109
75°	23261
80°	20638
85°	16799

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 57.5°
 Luminance: 27188 cd/sqm



TEST NUMBER: P748173

CATALOG NUMBER: LD4D40BD010-EU4DR7040509027-4LBSQW1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	233.4	10.3
10°-20°	640.1	28.1
20°-30°	705.0	31.0
30°-40°	269.4	11.8
40°-50°	127.2	5.6
50°-60°	126.4	5.6
60°-70°	101.2	4.4
70°-80°	58.2	2.6
80°-90°	15.8	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1578.6	69.3
0°-40°	1847.9	81.2
0°-60°	2101.5	92.3
0°-90°	2276.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2276.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2560	
5°	2474	233
15°	2302	640
25°	1515	705
35°	343	269
45°	166	127
55°	142	126
65°	103	101
75°	55	58
85°	13	16
90°	0	



TEST NUMBER: P748173

CATALOG NUMBER: LD4D40BD010-EU4DR7040509027-4LBSQW1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	2559.8
2.5°	2533.0
5°	2474.3
7.5°	2425.2
10°	2377.8
12.5°	2337.7
15°	2301.6
17.5°	2214.5
20°	2090.9
22.5°	1824.2
25°	1515.0
27.5°	1318.8
30°	1023.3
32.5°	661.0
35°	342.9
37.5°	185.2
40°	168.6
42.5°	167.4
45°	165.8
47.5°	162.1
50°	156.0
52.5°	149.1
55°	141.9
57.5°	133.7
60°	124.4
62.5°	113.9
65°	102.9
67.5°	90.8
70°	78.6
72.5°	66.5
75°	55.1
77.5°	43.4
80°	32.8
82.5°	23.1
85°	13.4
87.5°	5.3
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)