

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P740665

Luminaire Tested: LD4D05D010-EU4DR650210IC9035-4LBSQW1B

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P740665
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-59)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D05D010-EU4DR650210IC9035-4LBSQW1B
Description: 4 INCH SQAURE DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3500K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 449.9 lumens
Efficiency: N/A
Efficacy: 60.0 lumens/watt
Spacing Criteria (0/90/45): 0.98 / 0.98 / 0.92
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 7.5
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P740665
CATALOG NUMBER: LD4D05D010-EU4DR650210IC9035-4LBSQW1B

Luminous Intensity Polar Plot





TEST NUMBER: P740665
 CATALOG NUMBER: LD4D05D010-EU4DR650210IC9035-4LBSQW1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20	
RC	80					70					50					30					10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100	
1	113	111	108	106	111	108	106	104	104	103	101	101	99	98	97	96	95	93			93	
2	108	103	99	95	106	101	97	94	98	95	92	95	92	90	92	90	88	87			87	
3	102	96	91	87	100	94	90	86	92	88	85	89	86	83	87	84	82	80			80	
4	97	89	84	79	95	88	83	79	86	82	78	84	80	77	82	79	76	75			75	
5	92	83	78	73	90	83	77	73	81	76	72	79	75	72	77	74	71	69			69	
6	87	78	72	68	86	77	72	68	76	71	67	74	70	67	73	69	66	65			65	
7	83	73	67	63	81	73	67	63	71	66	62	70	66	62	69	65	62	60			60	
8	79	69	63	59	77	68	63	59	67	62	58	66	62	58	65	61	58	57			57	
9	75	65	59	55	74	65	59	55	64	58	55	63	58	55	62	58	54	53			53	
10	71	61	56	52	70	61	55	52	60	55	51	59	55	51	59	54	51	50			50	

AVERAGE LUMINANCE (cd/sqm):

0°	
0°	48381
5°	48423
10°	50126
15°	50212
20°	46230
25°	39398
30°	30153
35°	21301
40°	12580
45°	5115
50°	1853
55°	1029
60°	590
65°	336
70°	351
75°	253
80°	315
85°	251

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 5115 cd/sqm



TEST NUMBER: P740665

CATALOG NUMBER: LD4D05D010-EU4DR650210IC9035-4LBSQW1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	42.6	9.5
10°-20°	123.0	27.3
20°-30°	147.6	32.8
30°-40°	99.2	22.0
40°-50°	29.7	6.6
50°-60°	5.2	1.2
60°-70°	1.5	0.3
70°-80°	0.7	0.2
80°-90°	0.2	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	313.2	69.6
0°-40°	412.4	91.7
0°-60°	447.4	99.5
0°-90°	449.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	449.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	443	
5°	442	43
15°	444	123
25°	327	148
35°	160	99
45°	33	30
55°	5	5
65°	1	2
75°	1	1
85°	0	0
90°	0	



TEST NUMBER: P740665

CATALOG NUMBER: LD4D05D010-EU4DR650210IC9035-4LBSQW1B

CANDELA DISTRIBUTION (FULL):

0°	
0°	442.8
2.5°	444.7
5°	441.5
7.5°	448.2
10°	451.8
12.5°	451.0
15°	443.9
17.5°	426.7
20°	397.6
22.5°	363.4
25°	326.8
27.5°	285.4
30°	239.0
32.5°	197.0
35°	159.7
37.5°	122.9
40°	88.2
42.5°	57.6
45°	33.1
47.5°	17.5
50°	10.9
52.5°	7.6
55°	5.4
57.5°	3.9
60°	2.7
62.5°	1.8
65°	1.3
67.5°	1.1
70°	1.1
72.5°	0.8
75°	0.6
77.5°	0.6
80°	0.5
82.5°	0.3
85°	0.2
87.5°	0.1
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)