

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P740213

Luminaire Tested: LD4D05D010-EU4DR350210IC9050-4LBCSSQMMS

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P740213
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-20)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D05D010-EU4DR350210IC9050-4LBCSSQMMS
Description: 4 INCH SQAURE SHALLOW CAST MATTE METALLIC SILVER TRIM, WITH 35° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 5000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 626.1 lumens
Efficiency: N/A
Efficacy: 83.5 lumens/watt
Spacing Criteria (0/90/45): 0.6 / 0.6 / 0.54
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 7.5
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P740213
CATALOG NUMBER: LD4D05D010-EU4DR350210IC9050-4LBCSSQMMS

Luminous Intensity Polar Plot





TEST NUMBER: P740213
 CATALOG NUMBER: LD4D05D010-EU4DR350210IC9050-4LBCSSQMMS

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20	
RC	80					70					50					30					10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100				
1	115	112	110	108	112	110	108	107	106	105	103	103	101	100	99	98	98	96				
2	110	106	103	101	108	105	102	99	102	99	97	99	97	95	96	95	93	92				
3	106	101	97	94	105	100	96	93	97	95	92	95	93	91	93	91	89	88				
4	103	97	92	89	101	96	92	89	94	90	88	92	89	87	90	88	86	84				
5	99	93	88	85	98	92	87	84	90	86	84	89	85	83	87	84	82	81				
6	96	89	84	81	94	88	84	81	87	83	80	85	82	80	84	81	79	78				
7	93	85	81	77	91	85	80	77	84	80	77	83	79	77	82	79	76	75				
8	90	82	78	74	88	82	77	74	81	77	74	80	76	74	79	76	73	72				
9	87	79	75	72	86	79	75	72	78	74	71	77	74	71	77	73	71	70				
10	84	77	72	69	83	76	72	69	76	72	69	75	71	69	74	71	69	68				

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	188224
5°	183799
10°	165654
15°	128578
20°	72926
25°	28379
30°	10585
35°	5802
40°	3794
45°	2318
50°	1479
55°	1029
60°	765
65°	414
70°	32
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 2318 cd/sqm



TEST NUMBER: P740213

CATALOG NUMBER: LD4D05D010-EU4DR350210IC9050-4LBCSSQMMS

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	154.1	24.6
10°-20°	300.9	48.1
20°-30°	122.7	19.6
30°-40°	29.4	4.7
40°-50°	12.3	2.0
50°-60°	5.1	0.8
60°-70°	1.6	0.3
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	577.8	92.3
0°-40°	607.1	97.0
0°-60°	624.5	99.7
0°-90°	626.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	626.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1723	
5°	1676	154
15°	1137	301
25°	235	123
35°	44	29
45°	15	12
55°	5	5
65°	2	2
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P740213
CATALOG NUMBER: LD4D05D010-EU4DR350210IC9050-4LBCSSQMMS

CANDELA DISTRIBUTION (FULL):

	0°
0°	1722.7
2.5°	1712.4
5°	1675.8
7.5°	1602.9
10°	1493.1
12.5°	1338.5
15°	1136.7
17.5°	889.8
20°	627.2
22.5°	399.9
25°	235.4
27.5°	133.0
30°	83.9
32.5°	58.9
35°	43.5
37.5°	33.6
40°	26.6
42.5°	20.5
45°	15.0
47.5°	11.2
50°	8.7
52.5°	6.9
55°	5.4
57.5°	4.4
60°	3.5
62.5°	2.5
65°	1.6
67.5°	0.6
70°	0.1
72.5°	0.1
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.1
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)