

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P751231

Luminaire Tested: LD4D60D010-EU4DR6555659035-4LBCSSQMMS

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P751231
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-147)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D60D010-EU4DR6555659035-4LBCSSQMMS
Description: 4 INCH SQAURE SHALLOW CAST MATTE METALLIC SILVER TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3500K CCT
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 5350.2 lumens
Efficiency: N/A
Efficacy: 83.1 lumens/watt
Spacing Criteria (0/90/45): 0.95 / 0.95 / 0.96
Luminous Opening: Circular (Dia: 0.48' x H: 0')
CIE Type: Direct

Input Watts (W): 64.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P751231
CATALOG NUMBER: LD4D60D010-EU4DR6555659035-4LBCSSQMMS

Luminous Intensity Polar Plot





TEST NUMBER: P751231

CATALOG NUMBER: LD4D60D010-EU4DR6555659035-4LBCSSQMMS

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100																
1	113	110	107	105	111	108	105	103	104	102	100	100	99	97	97	95	94	93			93																
2	107	102	97	94	105	100	96	92	97	93	90	94	91	88	91	89	87	85			85																
3	101	94	88	84	99	92	87	83	90	86	82	87	84	81	85	82	80	78			78																
4	95	87	81	76	93	86	80	76	84	79	75	82	77	74	80	76	73	72			72																
5	90	81	74	70	88	80	74	69	78	73	69	76	72	68	75	71	68	66			66																
6	85	75	69	64	83	74	68	64	73	67	63	71	67	63	70	66	62	61			61																
7	80	70	64	59	79	69	63	59	68	63	59	67	62	58	66	61	58	56			56																
8	76	66	59	55	75	65	59	55	64	58	54	63	58	54	62	57	54	52			52																
9	72	61	55	51	71	61	55	51	60	54	51	59	54	50	58	54	50	49			49																
10	68	58	52	47	67	57	51	47	57	51	47	56	51	47	55	50	47	46			46																

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	283720
5°	283004
10°	282760
15°	274048
20°	249485
25°	217406
30°	180824
35°	143273
40°	103413
45°	65333
50°	34054
55°	18104
60°	9508
65°	5224
70°	2186
75°	2415
80°	1682
85°	1407

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 65333 cd/sqm



TEST NUMBER: P751231

CATALOG NUMBER: LD4D60D010-EU4DR6555659035-4LBCSSQMMS

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	459.4	8.6
10°-20°	1258.0	23.5
20°-30°	1537.7	28.7
30°-40°	1247.7	23.3
40°-50°	621.8	11.6
50°-60°	173.4	3.2
60°-70°	39.4	0.7
70°-80°	10.2	0.2
80°-90°	2.6	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3255.1	60.8
0°-40°	4502.8	84.2
0°-60°	5298.0	99.0
0°-90°	5350.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5350.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	4858	
5°	4827	459
15°	4532	1258
25°	3374	1538
35°	2010	1248
45°	791	622
55°	178	173
65°	38	39
75°	11	10
85°	2	3
90°	0	



TEST NUMBER: P751231

CATALOG NUMBER: LD4D60D010-EU4DR6555659035-4LBCSSQMMS

CANDELA DISTRIBUTION (FULL):

	0°
0°	4857.9
2.5°	4854.3
5°	4827.2
7.5°	4811.5
10°	4767.9
12.5°	4679.4
15°	4532.4
17.5°	4302.5
20°	4014.1
22.5°	3702.8
25°	3373.7
27.5°	3021.8
30°	2681.3
32.5°	2345.1
35°	2009.5
37.5°	1674.7
40°	1356.4
42.5°	1058.0
45°	791.0
47.5°	551.1
50°	374.8
52.5°	258.4
55°	177.8
57.5°	119.9
60°	81.4
62.5°	56.4
65°	37.8
67.5°	19.3
70°	12.8
72.5°	12.1
75°	10.7
77.5°	7.1
80°	5.0
82.5°	3.6
85°	2.1
87.5°	1.4
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)