

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P751917

Luminaire Tested: LD4D65D010-EU4DR6055659027-4LBSQW1B

Issue Date: 2/5/2024

**Test Information**

Test Method: LM-79-2019  
Report Number: P751917  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-57)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 2/5/2024  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: PORTFOLIO  
Catalog Number: LD4D65D010-EU4DR6055659027-4LBSQW1B  
Description: 4 INCH SQAURE DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 60° OPTIC  
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 5168.9 lumens  
Efficiency: N/A  
Efficacy: 71.0 lumens/watt  
Spacing Criteria (0/90/45): 0.91 / 0.91 / 0.83  
Luminous Opening: Circular (Dia: 0.35' x H: 0')  
CIE Type: Direct


Input Watts (W): 72.8  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT



TEST NUMBER: P751917

CATALOG NUMBER: LD4D65D010-EU4DR6055659027-4LBSQW1B

### Luminous Intensity Polar Plot





TEST NUMBER: P751917

CATALOG NUMBER: LD4D65D010-EU4DR6055659027-4LBSQW1B

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	113	110	108	105	111	108	106	104	104	102	100	100	99	97	97	96	95	93																			
2	107	102	98	95	105	101	97	94	97	94	92	94	92	90	92	90	88	86																			
3	102	96	90	86	100	94	89	86	91	88	84	89	86	83	87	84	82	80																			
4	97	89	84	80	95	88	83	79	86	82	78	84	80	77	82	79	76	75																			
5	92	84	78	74	91	83	78	74	81	77	73	80	76	72	78	75	72	70																			
6	88	79	73	69	87	78	73	69	77	72	68	75	71	68	74	70	67	66																			
7	84	75	69	65	83	74	68	64	73	68	64	72	67	64	71	67	63	62																			
8	80	71	65	61	79	70	65	61	69	64	60	68	64	60	67	63	60	59																			
9	77	67	61	57	75	67	61	57	66	61	57	65	60	57	64	60	57	55																			
10	73	64	58	54	72	63	58	54	62	58	54	62	57	54	61	57	54	53																			

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	670719
5°	687210
10°	695511
15°	662571
20°	584178
25°	472507
30°	319610
35°	160153
40°	25973
45°	25434
50°	25939
55°	26326
60°	27053
65°	27689
70°	28336
75°	28664
80°	27622
85°	23067

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 75°  
 Luminance: 28664 cd/sqm



TEST NUMBER: P751917

CATALOG NUMBER: LD4D65D010-EU4DR6055659027-4LBSQW1B

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	598.8	11.6
10°-20°	1620.2	31.3
20°-30°	1743.2	33.7
30°-40°	757.7	14.7
40°-50°	127.3	2.5
50°-60°	123.7	2.4
60°-70°	105.9	2.0
70°-80°	70.8	1.4
80°-90°	21.2	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3962.3	76.7
0°-40°	4720.0	91.3
0°-60°	4971.0	96.2
0°-90°	5168.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5168.9	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	6139	
5°	6266	599
15°	5858	1620
25°	3919	1743
35°	1201	758
45°	165	127
55°	138	124
65°	107	106
75°	68	71
85°	18	21
90°	0	



TEST NUMBER: P751917

CATALOG NUMBER: LD4D65D010-EU4DR6055659027-4LBSQW1B

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	6138.7
2.5°	6311.2
5°	6265.7
7.5°	6280.1
10°	6268.9
12.5°	6139.5
15°	5857.5
17.5°	5478.8
20°	5024.2
22.5°	4537.7
25°	3919.4
27.5°	3134.8
30°	2533.3
32.5°	1952.5
35°	1200.7
37.5°	513.7
40°	182.1
42.5°	167.8
45°	164.6
47.5°	159.0
50°	152.6
52.5°	145.4
55°	138.2
57.5°	131.0
60°	123.8
62.5°	115.8
65°	107.1
67.5°	98.3
70°	88.7
72.5°	78.3
75°	67.9
77.5°	55.9
80°	43.9
82.5°	31.2
85°	18.4
87.5°	6.4
90°	0.0

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report





Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)