

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P751632

Luminaire Tested: LD4D65D010-EU4DR4055659035-4LBSQW1MW

Issue Date: 1/30/2024

**Test Information**

Test Method: LM-79-2019  
Report Number: P751632  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-28)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 1/30/2024  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: PORTFOLIO  
Catalog Number: LD4D65D010-EU4DR4055659035-4LBSQW1MW  
Description: 4 INCH SQAURE DEEP 45° CUTOFF MATTE WHITE TRIM, WITH 40° OPTIC  
Light Source: (1) HIGH LUMEN LED 90CRI / 3500K CCT  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 6363.7 lumens  
Efficiency: N/A  
Efficacy: 87.4 lumens/watt  
Spacing Criteria (0/90/45): 0.68 / 0.68 / 0.6  
Luminous Opening: Circular (Dia: 0.35' x H: 0')  
CIE Type: Direct


Input Watts (W): 72.8  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT



TEST NUMBER: P751632

CATALOG NUMBER: LD4D65D010-EU4DR4055659035-4LBSQW1MW

### Luminous Intensity Polar Plot





TEST NUMBER: P751632

CATALOG NUMBER: LD4D65D010-EU4DR4055659035-4LBSQW1MW

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20					20					20					20					20					
RC	80					70					50					30					10					0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																										
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100					100			
1	115	112	110	108	112	110	108	107	106	105	103	103	101	100	99	98	97	96					96			
2	110	106	103	100	108	105	102	99	102	99	97	99	97	95	96	95	93	92					92			
3	106	101	97	94	104	100	96	93	97	94	92	95	93	90	93	91	89	88					88			
4	102	97	92	89	101	95	91	88	93	90	87	92	89	86	90	87	85	84					84			
5	99	92	88	84	97	91	87	84	90	86	83	88	85	83	87	84	82	81					81			
6	95	88	84	80	94	88	83	80	86	82	80	85	82	79	84	81	79	77					77			
7	92	85	80	77	91	84	80	77	83	79	76	82	79	76	81	78	76	74					74			
8	89	82	77	74	88	81	77	74	80	76	73	79	76	73	78	75	73	72					72			
9	86	79	74	71	85	78	74	71	77	73	71	76	73	70	76	72	70	69					69			
10	83	76	71	68	82	75	71	68	75	71	68	74	70	68	73	70	68	67					67			

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	1618862
5°	1610996
10°	1522738
15°	1294523
20°	882313
25°	368142
30°	115755
35°	53793
40°	29753
45°	13644
50°	6612
55°	3619
60°	1901
65°	672
70°	288
75°	0
80°	0
85°	0

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 45°  
 Luminance: 13644 cd/sqm



TEST NUMBER: P751632

CATALOG NUMBER: LD4D65D010-EU4DR4055659035-4LBSQW1MW

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	1371.5	21.6
10°-20°	3072.6	48.3
20°-30°	1538.0	24.2
30°-40°	281.9	4.4
40°-50°	77.8	1.2
50°-60°	18.3	0.3
60°-70°	3.5	0.1
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	5982.2	94.0
0°-40°	6264.1	98.4
0°-60°	6360.1	99.9
0°-90°	6363.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6363.7	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	14816	
5°	14688	###
15°	11444	3073
25°	3054	1538
35°	403	282
45°	88	78
55°	19	18
65°	3	4
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P751632

CATALOG NUMBER: LD4D65D010-EU4DR4055659035-4LBSQW1MW

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	14816.5
2.5°	14794.8
5°	14688.4
7.5°	14349.1
10°	13725.0
12.5°	12752.1
15°	11444.3
17.5°	9743.5
20°	7588.3
22.5°	5173.4
25°	3053.7
27.5°	1614.3
30°	917.5
32.5°	592.9
35°	403.3
37.5°	288.2
40°	208.6
42.5°	142.8
45°	88.3
47.5°	56.3
50°	38.9
52.5°	27.7
55°	19.0
57.5°	12.1
60°	8.7
62.5°	5.2
65°	2.6
67.5°	1.7
70°	0.9
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report





Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)