

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P752126

Luminaire Tested: LD4D65D010-EU4DR7055659050-4LBSQW1MW

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P752126
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-73)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D65D010-EU4DR7055659050-4LBSQW1MW
Description: 4 INCH SQAURE DEEP 45° CUTOFF MATTE WHITE TRIM, WITH 70° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 5000K CCT
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 5886.9 lumens
Efficiency: N/A
Efficacy: 80.9 lumens/watt
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.82
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 72.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P752126
CATALOG NUMBER: LD4D65D010-EU4DR7055659050-4LBSQW1MW

Luminous Intensity Polar Plot





TEST NUMBER: P752126

CATALOG NUMBER: LD4D65D010-EU4DR7055659050-4LBSQW1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

| | | | | | | | | | | | | | | | | | | | | | |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|-----|
| RF | 20 | | | | 20 | | | | 20 | | | | 20 | | | | 20 | | | | |
| RC | 80 | | | | 70 | | | | 50 | | | | 30 | | | | 10 | | | 0 | |
| RW | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 0 |
| RCR | | | | | | | | | | | | | | | | | | | | | |
| 0 | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 | 106 | 106 | 106 | 102 | 102 | 102 | 100 | | | 100 |
| 1 | 112 | 109 | 106 | 103 | 110 | 107 | 104 | 102 | 103 | 101 | 99 | 99 | 97 | 96 | 95 | 94 | 93 | 91 | | | 91 |
| 2 | 106 | 100 | 95 | 91 | 103 | 98 | 94 | 90 | 95 | 91 | 88 | 92 | 89 | 86 | 89 | 87 | 85 | 83 | | | 83 |
| 3 | 100 | 92 | 87 | 82 | 98 | 91 | 86 | 81 | 88 | 84 | 80 | 86 | 82 | 79 | 83 | 80 | 78 | 76 | | | 76 |
| 4 | 94 | 86 | 80 | 75 | 92 | 85 | 79 | 74 | 82 | 77 | 73 | 80 | 76 | 73 | 78 | 75 | 72 | 70 | | | 70 |
| 5 | 89 | 80 | 74 | 69 | 87 | 79 | 73 | 69 | 77 | 72 | 68 | 75 | 71 | 67 | 74 | 70 | 67 | 65 | | | 65 |
| 6 | 85 | 75 | 68 | 64 | 83 | 74 | 68 | 64 | 73 | 67 | 63 | 71 | 66 | 63 | 70 | 66 | 62 | 61 | | | 61 |
| 7 | 80 | 70 | 64 | 59 | 79 | 70 | 64 | 59 | 68 | 63 | 59 | 67 | 62 | 59 | 66 | 62 | 58 | 57 | | | 57 |
| 8 | 77 | 66 | 60 | 56 | 75 | 66 | 60 | 56 | 65 | 59 | 55 | 64 | 59 | 55 | 63 | 58 | 55 | 53 | | | 53 |
| 9 | 73 | 63 | 57 | 52 | 72 | 62 | 56 | 52 | 61 | 56 | 52 | 60 | 55 | 52 | 60 | 55 | 52 | 50 | | | 50 |
| 10 | 70 | 59 | 53 | 49 | 69 | 59 | 53 | 49 | 58 | 53 | 49 | 57 | 52 | 49 | 57 | 52 | 49 | 48 | | | 48 |

AVERAGE LUMINANCE (cd/sqm):

| | |
|-----|--------|
| | 0° |
| 0° | 723153 |
| 5° | 701666 |
| 10° | 682109 |
| 15° | 673159 |
| 20° | 628594 |
| 25° | 472230 |
| 30° | 333828 |
| 35° | 118244 |
| 40° | 62172 |
| 45° | 66226 |
| 50° | 68570 |
| 55° | 69872 |
| 60° | 70298 |
| 65° | 68821 |
| 70° | 64946 |
| 75° | 60157 |
| 80° | 53420 |
| 85° | 43375 |

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 57.5°
 Luminance: 70319 cd/sqm



TEST NUMBER: P752126

CATALOG NUMBER: LD4D65D010-EU4DR7055659050-4LBSQW1MW

ZONAL LUMENS:

| Zone | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10° | 603.4 | 10.3 |
| 10°-20° | 1655.2 | 28.1 |
| 20°-30° | 1822.9 | 31.0 |
| 30°-40° | 696.5 | 11.8 |
| 40°-50° | 328.9 | 5.6 |
| 50°-60° | 326.9 | 5.6 |
| 60°-70° | 261.8 | 4.4 |
| 70°-80° | 150.5 | 2.6 |
| 80°-90° | 40.9 | 0.7 |
| 90°-100° | 0.0 | 0.0 |
| 100°-110° | 0.0 | 0.0 |
| 110°-120° | 0.0 | 0.0 |
| 120°-130° | 0.0 | 0.0 |
| 130°-140° | 0.0 | 0.0 |
| 140°-150° | 0.0 | 0.0 |
| 150°-160° | 0.0 | 0.0 |
| 160°-170° | 0.0 | 0.0 |
| 170°-180° | 0.0 | 0.0 |
| 0°-30° | 4081.5 | 69.3 |
| 0°-40° | 4778.0 | 81.2 |
| 0°-60° | 5433.8 | 92.3 |
| 0°-90° | 5886.9 | 100.0 |
| 90°-120° | 0.0 | 0.0 |
| 90°-150° | 0.0 | 0.0 |
| 90°-180° | 0.0 | 0.0 |
| 0°-180° | 5886.9 | 100.0 |

CANDELA DISTRIBUTION:

| | 0° | Flux |
|-----|------|------|
| 0° | 6619 | |
| 5° | 6398 | 603 |
| 15° | 5951 | 1655 |
| 25° | 3917 | 1823 |
| 35° | 886 | 696 |
| 45° | 429 | 329 |
| 55° | 367 | 327 |
| 65° | 266 | 262 |
| 75° | 142 | 150 |
| 85° | 35 | 41 |
| 90° | 0 | |



TEST NUMBER: P752126

CATALOG NUMBER: LD4D65D010-EU4DR7055659050-4LBSQW1MW

CANDELA DISTRIBUTION (FULL):

| 0° | |
|-------|--------|
| 0° | 6618.6 |
| 2.5° | 6549.4 |
| 5° | 6397.5 |
| 7.5° | 6270.7 |
| 10° | 6148.1 |
| 12.5° | 6044.3 |
| 15° | 5951.1 |
| 17.5° | 5725.8 |
| 20° | 5406.2 |
| 22.5° | 4716.6 |
| 25° | 3917.1 |
| 27.5° | 3409.9 |
| 30° | 2646.0 |
| 32.5° | 1709.1 |
| 35° | 886.5 |
| 37.5° | 478.9 |
| 40° | 435.9 |
| 42.5° | 432.8 |
| 45° | 428.6 |
| 47.5° | 419.2 |
| 50° | 403.4 |
| 52.5° | 385.6 |
| 55° | 366.8 |
| 57.5° | 345.8 |
| 60° | 321.7 |
| 62.5° | 294.5 |
| 65° | 266.2 |
| 67.5° | 234.7 |
| 70° | 203.3 |
| 72.5° | 171.9 |
| 75° | 142.5 |
| 77.5° | 112.1 |
| 80° | 84.9 |
| 82.5° | 59.7 |
| 85° | 34.6 |
| 87.5° | 13.6 |
| 90° | 0.0 |

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)