

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P752841

Luminaire Tested: LD4D70BD010-EU4DR7070959024-4LBSQW1MW

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P752841
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-73)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D70BD010-EU4DR7070959024-4LBSQW1MW
Description: 4 INCH SQAURE DEEP 45° CUTOFF MATTE WHITE TRIM, WITH 70° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2400K CCT
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 4826.6 lumens
Efficiency: N/A
Efficacy: 72.5 lumens/watt
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.82
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 66.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P752841
CATALOG NUMBER: LD4D70BD010-EU4DR7070959024-4LBSQW1MW

Luminous Intensity Polar Plot





TEST NUMBER: P752841

CATALOG NUMBER: LD4D70BD010-EU4DR7070959024-4LBSQW1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	112	109	106	103	110	107	104	102	103	101	99	99	97	96	95	94	93	91																			
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	85	83																			
3	100	92	87	82	98	91	86	81	88	84	80	86	82	79	83	80	78	76																			
4	94	86	80	75	92	85	79	74	82	77	73	80	76	73	78	75	72	70																			
5	89	80	74	69	87	79	73	69	77	72	68	75	71	67	74	70	67	65																			
6	85	75	68	64	83	74	68	64	73	67	63	71	66	63	70	66	62	61																			
7	80	70	64	59	79	70	64	59	68	63	59	67	62	59	66	62	58	57																			
8	77	66	60	56	75	66	60	56	65	59	55	64	59	55	63	58	55	53																			
9	73	63	57	52	72	62	56	52	61	56	52	60	55	52	60	55	52	50																			
10	70	59	53	49	69	59	53	49	58	53	49	57	52	49	57	52	49	48																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	592893
5°	575284
10°	559247
15°	551911
20°	515368
25°	387165
30°	273699
35°	96943
40°	50976
45°	54298
50°	56229
55°	57280
60°	57646
65°	56412
70°	53253
75°	49307
80°	43793
85°	35603

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 57.5°
 Luminance: 57650 cd/sqm



TEST NUMBER: P752841

CATALOG NUMBER: LD4D70BD010-EU4DR7070959024-4LBSQW1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	494.7	10.3
10°-20°	1357.0	28.1
20°-30°	1494.6	31.0
30°-40°	571.0	11.8
40°-50°	269.6	5.6
50°-60°	268.1	5.6
60°-70°	214.6	4.4
70°-80°	123.3	2.6
80°-90°	33.6	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3346.3	69.3
0°-40°	3917.4	81.2
0°-60°	4455.1	92.3
0°-90°	4826.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4826.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	5426	
5°	5245	495
15°	4879	1357
25°	3212	1495
35°	727	571
45°	351	270
55°	301	268
65°	218	215
75°	117	123
85°	28	34
90°	0	



TEST NUMBER: P752841

CATALOG NUMBER: LD4D70BD010-EU4DR7070959024-4LBSQW1MW

CANDELA DISTRIBUTION (FULL):

0°	
0°	5426.4
2.5°	5369.7
5°	5245.2
7.5°	5141.2
10°	5040.7
12.5°	4955.6
15°	4879.2
17.5°	4694.4
20°	4432.4
22.5°	3867.1
25°	3211.5
27.5°	2795.7
30°	2169.4
32.5°	1401.3
35°	726.8
37.5°	392.6
40°	357.4
42.5°	354.8
45°	351.4
47.5°	343.7
50°	330.8
52.5°	316.2
55°	300.7
57.5°	283.5
60°	263.8
62.5°	241.4
65°	218.2
67.5°	192.5
70°	166.7
72.5°	140.9
75°	116.8
77.5°	91.9
80°	69.6
82.5°	49.0
85°	28.4
87.5°	11.2
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)