

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P752854

Luminaire Tested: LD4D70BD010-EU4DR7070959027-4LBSQW1MW

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P752854
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-73)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D70BD010-EU4DR7070959027-4LBSQW1MW
Description: 4 INCH SQAURE DEEP 45° CUTOFF MATTE WHITE TRIM, WITH 70° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2700K CCT
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 5467.5 lumens
Efficiency: N/A
Efficacy: 82.1 lumens/watt
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.82
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 66.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P752854
CATALOG NUMBER: LD4D70BD010-EU4DR7070959027-4LBSQW1MW

Luminous Intensity Polar Plot





TEST NUMBER: P752854

CATALOG NUMBER: LD4D70BD010-EU4DR7070959027-4LBSQW1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	112	109	106	103	110	107	104	102	103	101	99	99	97	96	95	94	93	91																			
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	85	83																			
3	100	92	87	82	98	91	86	81	88	84	80	86	82	79	83	80	78	76																			
4	94	86	80	75	92	85	79	74	82	77	73	80	76	73	78	75	72	70																			
5	89	80	74	69	87	79	73	69	77	72	68	75	71	67	74	70	67	65																			
6	85	75	68	64	83	74	68	64	73	67	63	71	66	63	70	66	62	61																			
7	80	70	64	59	79	70	64	59	68	63	59	67	62	59	66	62	58	57																			
8	77	66	60	56	75	66	60	56	65	59	55	64	59	55	63	58	55	53																			
9	73	63	57	52	72	62	56	52	61	56	52	60	55	52	60	55	52	50																			
10	70	59	53	49	69	59	53	49	58	53	49	57	52	49	57	52	49	48																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	671626
5°	651663
10°	633503
15°	625187
20°	583794
25°	438582
30°	310034
35°	109827
40°	57751
45°	61514
50°	63691
55°	64881
60°	65294
65°	63909
70°	60313
75°	55893
80°	49582
85°	40241

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 57.5°
 Luminance: 65317 cd/sqm



TEST NUMBER: P752854

CATALOG NUMBER: LD4D70BD010-EU4DR7070959027-4LBSQW1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	560.4	10.3
10°-20°	1537.2	28.1
20°-30°	1693.0	31.0
30°-40°	646.9	11.8
40°-50°	305.4	5.6
50°-60°	303.7	5.6
60°-70°	243.1	4.4
70°-80°	139.7	2.6
80°-90°	38.0	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3790.7	69.3
0°-40°	4437.5	81.2
0°-60°	5046.6	92.3
0°-90°	5467.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5467.5	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	6147	
5°	5942	560
15°	5527	1537
25°	3638	1693
35°	823	647
45°	398	305
55°	341	304
65°	247	243
75°	132	140
85°	32	38
90°	0	



TEST NUMBER: P752854

CATALOG NUMBER: LD4D70BD010-EU4DR7070959027-4LBSQW1MW

CANDELA DISTRIBUTION (FULL):

	0°
0°	6147.0
2.5°	6082.7
5°	5941.6
7.5°	5823.9
10°	5710.0
12.5°	5613.6
15°	5527.0
17.5°	5317.8
20°	5020.9
22.5°	4380.5
25°	3638.0
27.5°	3166.9
30°	2457.4
32.5°	1587.4
35°	823.4
37.5°	444.8
40°	404.9
42.5°	401.9
45°	398.1
47.5°	389.3
50°	374.7
52.5°	358.2
55°	340.6
57.5°	321.2
60°	298.8
62.5°	273.5
65°	247.2
67.5°	218.0
70°	188.8
72.5°	159.6
75°	132.4
77.5°	104.1
80°	78.8
82.5°	55.5
85°	32.1
87.5°	12.7
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)