

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P752723

Luminaire Tested: LD4D70BD010-EU4DR6070959035-4LBSQW1B

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P752723
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-57)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D70BD010-EU4DR6070959035-4LBSQW1B
Description: 4 INCH SQAURE DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 60° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3500K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 5485.1 lumens
Efficiency: N/A
Efficacy: 82.4 lumens/watt
Spacing Criteria (0/90/45): 0.91 / 0.91 / 0.83
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct


Input Watts (W): 66.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P752723

CATALOG NUMBER: LD4D70BD010-EU4DR6070959035-4LBSQW1B

Luminous Intensity Polar Plot





TEST NUMBER: P752723

CATALOG NUMBER: LD4D70BD010-EU4DR6070959035-4LBSQW1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	113	110	108	105	111	108	106	104	104	102	100	100	99	97	97	96	95	93																			
2	107	102	98	95	105	101	97	94	97	94	92	94	92	90	92	90	88	86																			
3	102	96	90	86	100	94	89	86	91	88	84	89	86	83	87	84	82	80																			
4	97	89	84	80	95	88	83	79	86	82	78	84	80	77	82	79	76	75																			
5	92	84	78	74	91	83	78	74	81	77	73	80	76	72	78	75	72	70																			
6	88	79	73	69	87	78	73	69	77	72	68	75	71	68	74	70	67	66																			
7	84	75	69	65	83	74	68	64	73	68	64	72	67	64	71	67	63	62																			
8	80	71	65	61	79	70	65	61	69	64	60	68	64	60	67	63	60	59																			
9	77	67	61	57	75	67	61	57	66	61	57	65	60	57	64	60	57	55																			
10	73	64	58	54	72	63	58	54	62	58	54	62	57	54	61	57	54	53																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	711757
5°	729261
10°	738070
15°	703112
20°	619920
25°	501416
30°	339165
35°	169956
40°	27570
45°	26979
50°	27520
55°	27945
60°	28714
65°	29369
70°	30061
75°	30437
80°	29321
85°	24446

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 75°
 Luminance: 30437 cd/sqm



TEST NUMBER: P752723

CATALOG NUMBER: LD4D70BD010-EU4DR6070959035-4LBSQW1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	635.5	11.6
10°-20°	1719.3	31.3
20°-30°	1849.9	33.7
30°-40°	804.1	14.7
40°-50°	135.0	2.5
50°-60°	131.3	2.4
60°-70°	112.3	2.0
70°-80°	75.2	1.4
80°-90°	22.5	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	4204.7	76.7
0°-40°	5008.8	91.3
0°-60°	5275.2	96.2
0°-90°	5485.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5485.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	6514	
5°	6649	635
15°	6216	1719
25°	4159	1850
35°	1274	804
45°	175	135
55°	147	131
65°	114	112
75°	72	75
85°	20	22
90°	0	



TEST NUMBER: P752723

CATALOG NUMBER: LD4D70BD010-EU4DR6070959035-4LBSQW1B

CANDELA DISTRIBUTION (FULL):

0°	
0°	6514.3
2.5°	6697.4
5°	6649.1
7.5°	6664.3
10°	6652.5
12.5°	6515.1
15°	6215.9
17.5°	5814.0
20°	5331.6
22.5°	4815.3
25°	4159.2
27.5°	3326.7
30°	2688.3
32.5°	2072.0
35°	1274.2
37.5°	545.1
40°	193.3
42.5°	178.0
45°	174.6
47.5°	168.7
50°	161.9
52.5°	154.3
55°	146.7
57.5°	139.0
60°	131.4
62.5°	122.9
65°	113.6
67.5°	104.3
70°	94.1
72.5°	83.1
75°	72.1
77.5°	59.3
80°	46.6
82.5°	33.1
85°	19.5
87.5°	6.8
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)