

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P752894

Luminaire Tested: LD4D70BD010-EU4DR7070959050-4LBCSSQMB

Issue Date: 1/30/2024

Test Information

Test Method: LM-79-2019
Report Number: P752894
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-76)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 1/30/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D70BD010-EU4DR7070959050-4LBCSSQMB
Description: 4 INCH SQAURE SHALLOW CAST MATTE BLACK TRIM, WITH 70° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 5000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 7174.2 lumens
Efficiency: N/A
Efficacy: 107.7 lumens/watt
Spacing Criteria (0/90/45): 1.1 / 1.1 / 1.04
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct


Input Watts (W): 66.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P752894

CATALOG NUMBER: LD4D70BD010-EU4DR7070959050-4LBCSSQMB

Luminous Intensity Polar Plot





TEST NUMBER: P752894
 CATALOG NUMBER: LD4D70BD010-EU4DR7070959050-4LBCSSQMB

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20	
RC	80					70					50					30					10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100				
1	113	110	107	105	111	108	106	103	104	102	100	100	99	97	97	95	94	93				
2	107	102	97	94	105	100	96	92	97	93	90	94	91	88	91	89	87	85				
3	101	94	88	84	99	92	87	83	90	85	82	87	84	81	85	82	79	78				
4	95	87	81	76	93	86	80	76	83	78	75	81	77	74	79	76	73	71				
5	89	80	74	69	88	79	73	69	78	72	68	76	71	68	74	70	67	65				
6	84	75	68	63	83	74	68	63	72	67	63	71	66	62	69	65	62	60				
7	80	69	63	58	78	69	62	58	67	62	58	66	61	57	65	61	57	56				
8	75	65	58	54	74	64	58	54	63	57	53	62	57	53	61	56	53	51				
9	71	61	54	50	70	60	54	50	59	53	50	58	53	49	57	53	49	48				
10	67	57	50	46	66	56	50	46	55	50	46	55	50	46	54	49	46	44				

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	618689
5°	617148
10°	615807
15°	615640
20°	609619
25°	572665
30°	510520
35°	407044
40°	270283
45°	161580
50°	83766
55°	44022
60°	15581
65°	259
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 161580 cd/sqm



TEST NUMBER: P752894

CATALOG NUMBER: LD4D70BD010-EU4DR7070959050-4LBCSSQMB

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	535.1	7.5
10°-20°	1534.7	21.4
20°-30°	2165.0	30.2
30°-40°	1869.0	26.1
40°-50°	837.0	11.7
50°-60°	219.1	3.1
60°-70°	14.3	0.2
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	4234.9	59.0
0°-40°	6103.9	85.1
0°-60°	7159.9	99.8
0°-90°	7174.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	7174.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	5662	
5°	5627	535
15°	5443	1535
25°	4750	2165
35°	3052	1869
45°	1046	837
55°	231	219
65°	1	14
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P752894

CATALOG NUMBER: LD4D70BD010-EU4DR7070959050-4LBCSSQMB

CANDELA DISTRIBUTION (FULL):

	0°
0°	5662.5
2.5°	5656.4
5°	5626.9
7.5°	5602.4
10°	5550.5
12.5°	5503.7
15°	5442.6
17.5°	5372.3
20°	5243.0
22.5°	5030.2
25°	4750.2
27.5°	4425.3
30°	4046.5
32.5°	3583.2
35°	3051.7
37.5°	2465.2
40°	1895.0
42.5°	1439.8
45°	1045.7
47.5°	720.9
50°	492.8
52.5°	340.1
55°	231.1
57.5°	139.5
60°	71.3
62.5°	22.4
65°	1.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)