

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P741718

Luminaire Tested: LD4D08D010-EU4DR700210IC9024-4LBSQW1B

Issue Date: 2/5/2024

**Test Information**

Test Method: LM-79-2019  
Report Number: P741718  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-73)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 2/5/2024  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: PORTFOLIO  
Catalog Number: LD4D08D010-EU4DR700210IC9024-4LBSQW1B  
Description: 4 INCH SQAURE DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 70° OPTIC  
Light Source: (1) HIGH LUMEN LED 90CRI / 2400K CCT  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 406.5 lumens  
Efficiency: N/A  
Efficacy: 45.7 lumens/watt  
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.82  
Luminous Opening: Circular (Dia: 0.35' x H: 0')  
CIE Type: Direct

Input Watts (W): 8.9  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT




Downlight



TEST NUMBER: P741718  
CATALOG NUMBER: LD4D08D010-EU4DR700210IC9024-4LBSQW1B

### Luminous Intensity Polar Plot





TEST NUMBER: P741718  
 CATALOG NUMBER: LD4D08D010-EU4DR700210IC9024-4LBSQW1B

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	112	109	106	103	110	107	104	102	103	101	99	99	97	96	95	94	93	91																			
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	85	83																			
3	100	92	87	82	98	91	86	81	88	84	80	86	82	79	83	80	78	76																			
4	94	86	80	75	92	85	79	74	82	77	73	80	76	73	78	75	72	70																			
5	89	80	74	69	88	79	73	69	77	72	68	75	71	67	74	70	67	65																			
6	85	75	68	64	83	74	68	64	73	67	63	71	66	63	70	66	62	61																			
7	80	70	64	59	79	70	64	59	68	63	59	67	62	59	66	62	58	57																			
8	77	66	60	56	75	66	60	56	65	59	55	64	59	55	63	58	55	53																			
9	73	63	57	52	72	62	56	52	61	56	52	60	55	52	60	55	52	50																			
10	70	59	53	49	69	59	53	49	58	53	49	57	53	49	57	52	49	48																			

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	49954
5°	48467
10°	47119
15°	46502
20°	43416
25°	32610
30°	23063
35°	8163
40°	4293
45°	4574
50°	4725
55°	4819
60°	4851
65°	4757
70°	4472
75°	4179
80°	3649
85°	3009

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 57.5°  
 Luminance: 4860 cd/sqm



TEST NUMBER: P741718

CATALOG NUMBER: LD4D08D010-EU4DR700210IC9024-4LBSQW1B

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	41.7	10.3
10°-20°	114.3	28.1
20°-30°	125.9	31.0
30°-40°	48.1	11.8
40°-50°	22.7	5.6
50°-60°	22.6	5.5
60°-70°	18.1	4.4
70°-80°	10.4	2.6
80°-90°	2.8	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	281.9	69.3
0°-40°	330.0	81.2
0°-60°	375.3	92.3
0°-90°	406.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	406.5	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	457	
5°	442	42
15°	411	114
25°	270	126
35°	61	48
45°	30	23
55°	25	23
65°	18	18
75°	10	10
85°	2	3
90°	0	



TEST NUMBER: P741718

CATALOG NUMBER: LD4D08D010-EU4DR700210IC9024-4LBSQW1B

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	457.2
2.5°	452.4
5°	441.9
7.5°	433.2
10°	424.7
12.5°	417.5
15°	411.1
17.5°	395.5
20°	373.4
22.5°	325.8
25°	270.5
27.5°	235.5
30°	182.8
32.5°	118.1
35°	61.2
37.5°	33.1
40°	30.1
42.5°	29.9
45°	29.6
47.5°	28.9
50°	27.8
52.5°	26.6
55°	25.3
57.5°	23.9
60°	22.2
62.5°	20.3
65°	18.4
67.5°	16.2
70°	14.0
72.5°	11.9
75°	9.9
77.5°	7.7
80°	5.8
82.5°	4.1
85°	2.4
87.5°	0.9
90°	0.0

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report





Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)