

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P741744

Luminaire Tested: LD4D08D010-EU4DR700210IC9030-4LBSQW1B

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P741744
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-73)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D08D010-EU4DR700210IC9030-4LBSQW1B
Description: 4 INCH SQAURE DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 70° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 466.2 lumens
Efficiency: N/A
Efficacy: 52.4 lumens/watt
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.82
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 8.9
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P741744

CATALOG NUMBER: LD4D08D010-EU4DR700210IC9030-4LBSQW1B

Luminous Intensity Polar Plot





TEST NUMBER: P741744
 CATALOG NUMBER: LD4D08D010-EU4DR700210IC9030-4LBSQW1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	112	109	106	103	110	107	104	102	103	101	99	99	97	96	95	94	93	91																			
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	85	83																			
3	100	92	87	82	98	91	86	81	88	84	80	86	82	79	83	80	78	76																			
4	94	86	80	75	92	85	79	74	82	77	73	80	76	73	78	75	72	70																			
5	89	80	74	69	87	79	73	68	77	72	68	75	71	67	74	70	67	65																			
6	85	75	68	64	83	74	68	64	73	67	63	71	66	63	70	66	62	61																			
7	80	70	64	59	79	70	64	59	68	63	59	67	62	59	66	62	58	57																			
8	77	66	60	56	75	66	60	56	65	59	55	64	59	55	63	58	55	53																			
9	73	63	57	52	72	62	56	52	61	56	52	60	55	52	60	55	52	50																			
10	70	59	53	49	69	59	53	49	58	53	49	57	52	49	57	52	49	48																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	57253
5°	55552
10°	54009
15°	53300
20°	49776
25°	37384
30°	26431
35°	9363
40°	4921
45°	5238
50°	5439
55°	5524
60°	5572
65°	5455
70°	5143
75°	4770
80°	4216
85°	3510

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 57.5°
 Luminance: 5572 cd/sqm



TEST NUMBER: P741744

CATALOG NUMBER: LD4D08D010-EU4DR700210IC9030-4LBSQW1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	47.8	10.2
10°-20°	131.1	28.1
20°-30°	144.3	31.0
30°-40°	55.1	11.8
40°-50°	26.0	5.6
50°-60°	25.9	5.6
60°-70°	20.7	4.4
70°-80°	11.9	2.6
80°-90°	3.3	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	323.2	69.3
0°-40°	378.3	81.2
0°-60°	430.2	92.3
0°-90°	466.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	466.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	524	
5°	506	48
15°	471	131
25°	310	144
35°	70	55
45°	34	26
55°	29	26
65°	21	21
75°	11	12
85°	3	3
90°	0	



TEST NUMBER: P741744

CATALOG NUMBER: LD4D08D010-EU4DR700210IC9030-4LBSQW1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	524.0
2.5°	518.6
5°	506.5
7.5°	496.5
10°	486.8
12.5°	478.6
15°	471.2
17.5°	453.3
20°	428.1
22.5°	373.4
25°	310.1
27.5°	270.0
30°	209.5
32.5°	135.3
35°	70.2
37.5°	37.9
40°	34.5
42.5°	34.3
45°	33.9
47.5°	33.2
50°	32.0
52.5°	30.5
55°	29.0
57.5°	27.4
60°	25.5
62.5°	23.3
65°	21.1
67.5°	18.6
70°	16.1
72.5°	13.6
75°	11.3
77.5°	8.9
80°	6.7
82.5°	4.8
85°	2.8
87.5°	1.1
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)