

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P755024

Luminaire Tested: LD4D85BD010-EU4DR6070959024-4LBSQW1B

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P755024
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-57)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D85BD010-EU4DR6070959024-4LBSQW1B
Description: 4 INCH SQAURE DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 60° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2400K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 5555.6 lumens
Efficiency: N/A
Efficacy: 63.3 lumens/watt
Spacing Criteria (0/90/45): 0.91 / 0.91 / 0.83
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct


Input Watts (W): 87.7
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P755024

CATALOG NUMBER: LD4D85BD010-EU4DR6070959024-4LBSQW1B

Luminous Intensity Polar Plot





TEST NUMBER: P755024

CATALOG NUMBER: LD4D85BD010-EU4DR6070959024-4LBSQW1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100																
1	113	110	108	105	111	108	106	104	104	102	100	100	99	97	97	96	95	93			93																
2	107	102	98	95	105	101	97	94	97	94	92	94	92	90	92	90	88	86			86																
3	102	96	90	86	100	94	89	86	91	88	84	89	86	83	87	84	82	80			80																
4	97	89	84	80	95	88	83	79	86	82	78	84	80	77	82	79	76	75			75																
5	92	84	78	74	91	83	78	74	81	77	73	80	76	72	78	75	72	70			70																
6	88	79	73	69	87	78	73	69	77	72	68	75	71	68	74	70	67	66			66																
7	84	75	69	65	83	74	68	64	73	68	64	72	67	64	71	67	63	62			62																
8	80	71	65	61	79	70	65	61	69	64	60	68	64	60	67	63	60	59			59																
9	77	67	61	57	75	67	61	57	66	61	57	65	60	57	64	60	57	55			55																
10	73	64	58	54	72	63	58	54	62	58	54	62	57	54	61	57	54	53			53																

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	720902
5°	738627
10°	747545
15°	712138
20°	627885
25°	507854
30°	343518
35°	172144
40°	27927
45°	27334
50°	27877
55°	28288
60°	29085
65°	29757
70°	30444
75°	30817
80°	29699
85°	24696

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 75°
 Luminance: 30817 cd/sqm



TEST NUMBER: P755024

CATALOG NUMBER: LD4D85BD010-EU4DR6070959024-4LBSQW1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	643.6	11.6
10°-20°	1741.4	31.3
20°-30°	1873.6	33.7
30°-40°	814.4	14.7
40°-50°	136.8	2.5
50°-60°	133.0	2.4
60°-70°	113.8	2.0
70°-80°	76.1	1.4
80°-90°	22.8	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	4258.7	76.7
0°-40°	5073.1	91.3
0°-60°	5342.9	96.2
0°-90°	5555.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5555.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	6598	
5°	6734	644
15°	6296	1741
25°	4213	1874
35°	1291	814
45°	177	137
55°	148	133
65°	115	114
75°	73	76
85°	20	23
90°	0	



TEST NUMBER: P755024

CATALOG NUMBER: LD4D85BD010-EU4DR6070959024-4LBSQW1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	6598.0
2.5°	6783.4
5°	6734.5
7.5°	6750.0
10°	6737.9
12.5°	6598.8
15°	6295.7
17.5°	5888.7
20°	5400.1
22.5°	4877.2
25°	4212.6
27.5°	3369.4
30°	2722.8
32.5°	2098.6
35°	1290.6
37.5°	552.1
40°	195.8
42.5°	180.3
45°	176.9
47.5°	170.9
50°	164.0
52.5°	156.3
55°	148.5
57.5°	140.8
60°	133.1
62.5°	124.5
65°	115.1
67.5°	105.6
70°	95.3
72.5°	84.1
75°	73.0
77.5°	60.1
80°	47.2
82.5°	33.5
85°	19.7
87.5°	6.9
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)