

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P755206

Luminaire Tested: LD4D85BD010-EU4DR7070959030-4LBSQW1B

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P755206
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-73)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD4D85BD010-EU4DR7070959030-4LBSQW1B
Description: 4 INCH SQAURE DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 70° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3000K CCT
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 5051.6 lumens
Efficiency: N/A
Efficacy: 57.6 lumens/watt
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.82
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 87.7
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P755206
CATALOG NUMBER: LD4D85BD010-EU4DR7070959030-4LBSQW1B

Luminous Intensity Polar Plot





TEST NUMBER: P755206

CATALOG NUMBER: LD4D85BD010-EU4DR7070959030-4LBSQW1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	112	109	106	103	110	107	104	102	103	101	99	99	97	96	95	94	93	91																			
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	85	83																			
3	100	92	87	82	98	91	86	81	88	84	80	86	82	79	83	80	78	76																			
4	94	86	80	75	92	85	79	74	82	77	73	80	76	73	78	75	72	70																			
5	89	80	74	69	87	79	73	69	77	72	68	75	71	67	74	70	67	65																			
6	85	75	68	64	83	74	68	64	73	67	63	71	66	63	70	66	62	61																			
7	80	70	64	59	79	70	64	59	68	63	59	67	62	59	66	62	58	57																			
8	77	66	60	56	75	66	60	56	65	59	55	64	59	55	63	58	55	53																			
9	73	63	57	52	72	62	56	52	61	56	52	60	55	52	60	55	52	50																			
10	70	59	53	49	69	59	53	49	58	53	49	57	52	49	57	52	49	48																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	620546
5°	602111
10°	585330
15°	577645
20°	539401
25°	405225
30°	286454
35°	101464
40°	53358
45°	56832
50°	58847
55°	59947
60°	60334
65°	59049
70°	55713
75°	51629
80°	45806
85°	37233

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 57.5°
 Luminance: 60334 cd/sqm



TEST NUMBER: P755206

CATALOG NUMBER: LD4D85BD010-EU4DR7070959030-4LBSQW1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	517.8	10.3
10°-20°	1420.3	28.1
20°-30°	1564.3	31.0
30°-40°	597.6	11.8
40°-50°	282.2	5.6
50°-60°	280.5	5.6
60°-70°	224.6	4.4
70°-80°	129.1	2.6
80°-90°	35.1	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3502.4	69.3
0°-40°	4100.0	81.2
0°-60°	4662.8	92.3
0°-90°	5051.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5051.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	5680	
5°	5490	518
15°	5107	1420
25°	3361	1564
35°	761	598
45°	368	282
55°	315	281
65°	228	225
75°	122	129
85°	30	35
90°	0	



TEST NUMBER: P755206

CATALOG NUMBER: LD4D85BD010-EU4DR7070959030-4LBSQW1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	5679.5
2.5°	5620.2
5°	5489.8
7.5°	5381.0
10°	5275.8
12.5°	5186.7
15°	5106.7
17.5°	4913.4
20°	4639.1
22.5°	4047.4
25°	3361.3
27.5°	2926.1
30°	2270.5
32.5°	1466.6
35°	760.7
37.5°	410.9
40°	374.1
42.5°	371.4
45°	367.8
47.5°	359.7
50°	346.2
52.5°	330.9
55°	314.7
57.5°	296.7
60°	276.1
62.5°	252.7
65°	228.4
67.5°	201.4
70°	174.4
72.5°	147.5
75°	122.3
77.5°	96.2
80°	72.8
82.5°	51.3
85°	29.7
87.5°	11.7
90°	0.0

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)