

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P756740

Luminaire Tested: LD4D95BD010-EU4DR7070959024-4LBSQW1B

Issue Date: 2/5/2024

**Test Information**

Test Method: LM-79-2019  
Report Number: P756740  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-73)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 2/5/2024  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: PORTFOLIO  
Catalog Number: LD4D95BD010-EU4DR7070959024-4LBSQW1B  
Description: 4 INCH SQAURE DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 70° OPTIC  
Light Source: (1) HIGH LUMEN LED 90CRI / 2400K CCT  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 4703.5 lumens  
Efficiency: N/A  
Efficacy: 47.4 lumens/watt  
Spacing Criteria (0/90/45): 0.88 / 0.88 / 0.82  
Luminous Opening: Circular (Dia: 0.35' x H: 0')  
CIE Type: Direct

Input Watts (W): 99.2  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT



TEST NUMBER: P756740  
CATALOG NUMBER: LD4D95BD010-EU4DR7070959024-4LBSQW1B

### Luminous Intensity Polar Plot





TEST NUMBER: P756740

CATALOG NUMBER: LD4D95BD010-EU4DR7070959024-4LBSQW1B

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	112	109	106	103	110	107	104	102	103	101	99	99	97	96	95	94	93	91																			
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	85	83																			
3	100	92	87	82	98	91	86	81	88	84	80	86	82	79	83	80	78	76																			
4	94	86	80	75	92	85	79	74	82	77	73	80	76	73	78	75	72	70																			
5	89	80	74	69	87	79	73	69	77	72	68	75	71	67	74	70	67	65																			
6	85	75	68	64	83	74	68	64	73	67	63	71	66	63	70	66	62	61																			
7	80	70	64	59	79	70	64	59	68	63	59	67	62	59	66	62	58	57																			
8	77	66	60	56	75	66	60	56	65	59	55	64	59	55	63	58	55	53																			
9	73	63	57	52	72	62	56	52	61	56	52	60	55	52	60	55	52	50																			
10	70	59	53	49	69	59	53	49	58	53	49	57	52	49	57	52	49	48																			

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	577793
5°	560620
10°	544990
15°	537839
20°	502229
25°	377304
30°	266722
35°	94475
40°	49678
45°	52907
50°	54784
55°	55814
60°	56160
65°	54990
70°	51880
75°	48083
80°	42660
85°	34600

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 57.5°  
 Luminance: 56186 cd/sqm



TEST NUMBER: P756740

CATALOG NUMBER: LD4D95BD010-EU4DR7070959024-4LBSQW1B

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	482.1	10.3
10°-20°	1322.4	28.1
20°-30°	1456.5	31.0
30°-40°	556.5	11.8
40°-50°	262.7	5.6
50°-60°	261.2	5.6
60°-70°	209.1	4.4
70°-80°	120.2	2.6
80°-90°	32.7	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3261.1	69.3
0°-40°	3817.5	81.2
0°-60°	4341.5	92.3
0°-90°	4703.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4703.5	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	5288	
5°	5112	482
15°	4755	1322
25°	3130	1456
35°	708	556
45°	342	263
55°	293	261
65°	213	209
75°	114	120
85°	28	33
90°	0	



TEST NUMBER: P756740

CATALOG NUMBER: LD4D95BD010-EU4DR7070959024-4LBSQW1B

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	5288.2
2.5°	5232.9
5°	5111.5
7.5°	5010.2
10°	4912.2
12.5°	4829.3
15°	4754.8
17.5°	4574.8
20°	4319.4
22.5°	3768.5
25°	3129.7
27.5°	2724.5
30°	2114.1
32.5°	1365.6
35°	708.3
37.5°	382.6
40°	348.3
42.5°	345.8
45°	342.4
47.5°	334.9
50°	322.3
52.5°	308.1
55°	293.0
57.5°	276.3
60°	257.0
62.5°	235.3
65°	212.7
67.5°	187.5
70°	162.4
72.5°	137.3
75°	113.9
77.5°	89.6
80°	67.8
82.5°	47.7
85°	27.6
87.5°	10.9
90°	0.0

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report





Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



— 0°-180°

Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



Signify Classified - Internal  
Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269

Scaled Data Report



(END OF REPORT)