

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P207543

Luminaire Tested: **LD4B10D010 EU4B10209024 4LBMMW1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P207543
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD4B10D010 EU4B10209024 4LBMMW1
Description: PORTFOLIO 4 INCH 50 DEGREE CUTOFF RECESSED DOWNLIGHT
MEDIUM DISTRIBUTION WITH MATTE WHITE TRIM
WATTAGE D010TR-10.05W DE010-10.58W D5LT-10.2W DMX-10.6W DL2-11.8W
DL3-11.1W DLE-11.39W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 607.0 lumens
Efficiency: N/A
Efficacy: 61.3 lumens/watt
Spacing Criteria (0/90/45): 0.99 / 0.99 / 0.97
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 9.9
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P207543

CATALOG NUMBER: LD4B10D010 EU4B10209024 4LBMMW1

Luminous Intensity Polar Plot





TEST NUMBER: P207543

CATALOG NUMBER: LD4B10D010 EU4B10209024 4LBMMW1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100
1	112	108	105	102	109	106	103	100	102	99	97	98	96	94	94	93	91	89			89
2	104	98	92	88	102	96	91	87	93	89	85	89	86	83	87	84	81	80			80
3	97	89	83	77	95	87	82	77	85	80	76	82	78	74	80	76	73	71			71
4	91	81	74	69	89	80	74	69	78	72	68	76	71	67	74	69	66	64			64
5	85	75	67	62	83	74	67	62	72	66	61	70	65	61	68	64	60	58			58
6	80	69	62	56	78	68	61	56	66	60	56	65	59	55	63	59	55	53			53
7	75	64	57	52	74	63	56	51	62	56	51	60	55	51	59	54	50	49			49
8	71	59	52	47	69	59	52	47	58	51	47	56	51	47	55	50	47	45			45
9	67	55	48	44	66	55	48	44	54	48	44	53	47	43	52	47	43	42			42
10	63	52	45	41	62	51	45	41	51	45	40	50	44	40	49	44	40	39			39

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P207543

CATALOG NUMBER: LD4B10D010 EU4B10209024 4LBMMW1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	42.7	7.0
10°-20°	114.5	18.9
20°-30°	152.2	25.1
30°-40°	124.5	20.5
40°-50°	72.5	11.9
50°-60°	48.1	7.9
60°-70°	31.6	5.2
70°-80°	16.7	2.7
80°-90°	4.1	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	309.4	51.0
0°-40°	433.9	71.5
0°-60°	554.6	91.4
0°-90°	607.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	607.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	461	
5°	456	43
15°	408	114
25°	334	152
35°	199	125
45°	92	73
55°	54	48
65°	32	32
75°	16	17
85°	4	4
90°	0	



TEST NUMBER: P207543

CATALOG NUMBER: LD4B10D010 EU4B10209024 4LBMMW1

CANDELA DISTRIBUTION (FULL):

	0°
0°	460.8
2.5°	459.9
5°	455.5
7.5°	444.9
10°	433.5
12.5°	423.0
15°	408.0
17.5°	391.3
20°	377.2
22.5°	357.9
25°	334.1
27.5°	308.6
30°	276.1
32.5°	237.4
35°	198.7
37.5°	163.6
40°	132.8
42.5°	109.0
45°	91.5
47.5°	77.4
50°	67.7
52.5°	59.8
55°	53.6
57.5°	47.5
60°	41.3
62.5°	36.9
65°	31.7
67.5°	27.3
70°	22.9
72.5°	19.3
75°	15.8
77.5°	12.3
80°	8.8
82.5°	6.2
85°	3.5
87.5°	0.9
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)