

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P206715

Luminaire Tested: **LD4B10D010 EU4B10208030 4LBWWH1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P206715
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD4B10D010 EU4B10208030 4LBWWH1
Description: PORTFOLIO 4 INCH 60 DEGREE CUTOFF RECESSED DOWNLIGHT
WIDE DISTRIBUTION WITH WHEAT TRIM
WATTAGE D010TR-10.05W DE010-10.58W D5LT-10.2W DMX-10.6W DL2-11.8W
DL3-11.1W DLE-11.39W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 931.7 lumens
Efficiency: N/A
Efficacy: 94.1 lumens/watt
Spacing Criteria (0/90/45): 1.26 / 1.26 / 1.16
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 9.9
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P206715

CATALOG NUMBER: LD4B10D010 EU4B10208030 4LBWWH1

Luminous Intensity Polar Plot





TEST NUMBER: P206715

CATALOG NUMBER: LD4B10D010 EU4B10208030 4LBWWH1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				20	
RC	80				70				50				30				10				0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100				100
1	113	110	107	104	110	107	105	103	103	101	100	100	98	97	96	95	94	92				92
2	106	101	96	92	104	99	95	91	96	92	89	93	90	87	90	88	85	84				84
3	100	93	87	82	98	91	86	82	88	84	80	86	82	79	84	80	78	76				76
4	94	85	79	74	92	84	78	74	82	77	73	80	75	72	78	74	71	69				69
5	88	79	72	67	86	78	71	67	76	70	66	74	69	65	72	68	65	63				63
6	83	73	66	61	81	72	65	61	70	64	60	69	64	60	67	63	59	58				58
7	78	67	60	56	76	67	60	55	65	59	55	64	59	55	63	58	54	53				53
8	73	62	56	51	72	62	55	51	61	55	51	60	54	50	59	54	50	49				49
9	69	58	51	47	68	58	51	47	57	51	47	56	50	47	55	50	46	45				45
10	65	54	48	43	64	54	48	43	53	47	43	52	47	43	51	46	43	41				41

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P206715

CATALOG NUMBER: LD4B10D010 EU4B10208030 4LBWWH1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	56.4	6.1
10°-20°	174.6	18.7
20°-30°	268.6	28.8
30°-40°	259.1	27.8
40°-50°	135.1	14.5
50°-60°	28.4	3.1
60°-70°	6.6	0.7
70°-80°	2.6	0.3
80°-90°	0.2	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	499.6	53.6
0°-40°	758.8	81.4
0°-60°	922.3	99.0
0°-90°	931.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	931.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	582	
5°	587	56
15°	618	175
25°	589	269
35°	420	259
45°	172	135
55°	26	28
65°	6	7
75°	2	3
85°	0	0
90°	0	



TEST NUMBER: P206715

CATALOG NUMBER: LD4B10D010 EU4B10208030 4LBWWH1

CANDELA DISTRIBUTION (FULL):

	0°
0°	582.5
2.5°	583.7
5°	587.4
7.5°	592.3
10°	599.6
12.5°	609.3
15°	617.9
17.5°	622.7
20°	619.1
22.5°	611.8
25°	588.6
27.5°	560.6
30°	524.0
32.5°	475.3
35°	420.4
37.5°	360.7
40°	298.6
42.5°	236.4
45°	171.8
47.5°	115.8
50°	74.3
52.5°	45.1
55°	25.6
57.5°	15.8
60°	11.0
62.5°	8.5
65°	6.1
67.5°	4.9
70°	3.7
72.5°	3.7
75°	2.4
77.5°	1.2
80°	1.2
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)